

Index Of Sheets
(See Sheet IA)

STATE OF TENNESSEE DEPARTMENT OF TRANSPORTATION BUREAU OF ENGINEERING


TENN.	YEAR	SHEET NO.
	2014	1
FED. AID PROJ. NO.	HSIP-10(50)	
STATE PROJ. NO.	52003-3216-94	

LINCOLN COUNTY


S.R. 10 (U.S. 231, HUNTSVILLE HIGHWAY)
INTERSECTION WITH S.R. 275 (LINCOLN ROAD)
SIGNALIZATION AND INTERSECTION IMPROVEMENTS

CONSTRUCTION

STATE HIGHWAY NO. 10 F.A.H.S. NO. 10
STATE HIGHWAY NO. 275 F.A.H.S. NO. 275



PROJECT LOCATION
LINCOLN COUNTY



SCALE: 1" = 2640'

NO EXCLUSIONS
NO EQUATIONS

**UNOFFICIAL
SET
NOT FOR
BIDDING**

APPROVED: *Paul D. Degges*
PAUL D. DEGGES, CHIEF ENGINEER

DATE: _____

APPROVED: *John Schroer*
JOHN SCHROER, COMMISSIONER

TRAFFIC DATA (SR 10)	
ADT (2016)	11,090
ADT (2036)	14,420
DHV (2036)	1,648
D	55 - 45
T (ADT)	8 %
T (DHV)	5 %
V	55 MPH

TRAFFIC DATA (SR 275)	
ADT (2016)	3,510
ADT (2036)	4,560
DHV (2036)	552
D	55 - 45
T (ADT)	8 %
T (DHV)	5 %
V	45 MPH

U.S. DEPARTMENT OF TRANSPORTATION
FEDERAL HIGHWAY ADMINISTRATION

APPROVED: _____
DIVISION ADMINISTRATOR DATE

SPECIAL NOTES

PROPOSALS MAY BE REJECTED BY THE COMMISSIONER IF ANY OF THE UNIT PRICES CONTAINED THEREIN ARE OBVIOUSLY UNBALANCED, EITHER EXCESSIVE OR BELOW THE REASONABLE COST ANALYSIS VALUE.

THIS PROJECT TO BE CONSTRUCTED UNDER THE STANDARD SPECIFICATIONS OF THE TENNESSEE DEPARTMENT OF TRANSPORTATION DATED MARCH 1, 2006 AND ADDITIONAL SPECIFICATIONS AND SPECIAL PROVISIONS CONTAINED IN THE PLANS AND IN THE PROPOSAL CONTRACT.

ROADWAY LENGTH 0.012 MILES
BRIDGE LENGTH 0.000 MILES
BOX BRIDGE LENGTH 0.000 MILES
PROJECT LENGTH 0.012 MILES

TDOT C.E. MANAGER 1 Roland L. Jones, P.E.
DESIGNED BY RPM Transportation Consultants, LLC
DESIGNER Kristen D. Rice, P.E. CHECKED BY Daniel J. Spann, P.E., PTOE
P.E. NO. 52003-1216-94
PIN NO. 117862.00

INDEX

DESCRIPTION	SHT.
TITLE SHEET	1
INDEX AND STANDARD DRAWINGS	1A
ESTIMATED ROADWAY QUANTITIES	2
TYPICAL SECTIONS AND PAVEMENT SCHEDULE	2A
GENERAL NOTES AND SPECIAL NOTES	2B-2D
PRESENT LAYOUT	3
PROPOSED LAYOUT	3A
PROFILE	3B
SIDE ROAD PROFILES	3C
EROSION PREVENTION AND SEDIMENT CONTROL PLAN	4
PROPOSED CONTOURS	5
TRAFFIC CONTROL PLAN	6
PROPOSED SIGNAL LAYOUT	7
SIGNAL DETAILS	8
ROADWAY CROSS SECTIONS	9
UTILITIES INDEX, UTILITY OWNERS, AND UTILITY SHEETS	U1-1
NO PROJECT COMMITMENTS SHEET INCLUDED IN THIS SET OF PLANS	

STANDARD ROADWAY DRAWINGS

DWG. NO	REV.	DESCRIPTION	DWG. NO	REV.	DESCRIPTION
ROADWAY DESIGN STANDARDS					
RD-A-1	12-18-99	STANDARD ABBREVIATIONS	T-S-20	11-01-11	SIGN DETAILS
RD-L-1	10-26-94	STANDARD LEGEND	T-SG-2	07-29-04	LOOP LEAD-INS, CONDUIT AND PULL BOXES
RD-L-2	09-05-01	STANDARD LEGEND FOR UTILITY INSTALLATIONS	T-SG-3	11-11-04	STANDARD NOTES AND DETAILS OF INDUCTION LOOPS
RD-L-3	04-15-04	STANDARD LEGEND FOR SIGNALIZATION AND LIGHTING	T-SG-4		SPAN WIRE AND MESSENGER CABLE DETAILS
RD-L-4	04-15-04	STANDARD LEGEND FOR SIGNALIZATION AND LIGHTING	T-SG-5	07-29-04	CONTROLLER CABINET DETAILS
RD-L-5	05-01-08	STANDARD LEGEND FOR EROSION PREVENTION AND SEDIMENT CONTROL	T-SG-7	11-01-11	SIGNAL HEAD ASSEMBLIES AND PEDESTRIAN PUSH BUTTON SIGNS
RD-L-6	03-30-10	STANDARD LEGEND FOR EROSION PREVENTION AND SEDIMENT CONTROL	T-SG-7A	11-01-11	TYPICAL SIGN HEAD PLACEMENT
RD-L-7	05-24-12	STANDARD LEGEND FOR EROSION PREVENTION AND SEDIMENT CONTROL	T-SG-8	11-01-11	STRAIN POLE DETAILS FOR SPAN MOUNTED SIGNALS
RD01-S-11	04-04-03	DESIGN AND CONSTRUCTION DETAILS FOR ROADSIDE SLOPE DEVELOPMENT	T-SG-9	11-16-07	DETAILS OF CANTILEVER SIGNAL SUPPORT
RD01-S-11A	10-15-02	ROADSIDE DITCH DETAILS FOR ROADSIDE SLOPE DEVELOPMENT	T-SG-9A		MISCELLANEOUS SIGNAL DETAILS
RD01-TS-2B	10-15-02	DESIGN STANDARDS 4 AND 6 LANE COLLECTOR HIGHWAYS WITH FLUSH MEDIANS	T-SG-10	05-06-13	MAST ARM POLE AND STRAIN POLES FOUNDATION DETAILS
RD01-TS-3	10-15-02	DESIGN STANDARDS FOR 2-LANE ARTERIAL HIGHWAYS	T-SG-12	11-01-11	TYPICAL WIRING FOR SIGNAL HEADS AND DETECTION LOOPS
RD01-SD-1		INTERSECTION SIGHT DISTANCE DESIGN AND GENERAL NOTES	T-SG-13	06-01-09	FLASHING BEACON DETAIL
RD01-SD-4		INTERSECTION SIGHT DISTANCE 5-LANE AND 4-LANE UNDIVIDED ROADWAYS	T-FAB-1	05-27-97	FLASHING YELLOW ARROW BOARD
DRAINAGE – CULVERTS AND ENDWALL					
D-PB-1	01-02-13	STANDARD DETAILS FOR CONCRETE PIPE INSTALLATION	T-WZ-40	04-02-12	RIGHT LANE CLOSURES AT NEAR SIDE OF INTERSECTIONS
D-PE-18A	06-14-13	18" CONCRETE ENDWALL CROSS DRAIN	T-WZ-50	04-02-12	TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 2 OR 3 LANE MAJOR ROUTES
D-PE-18B		18" CONCRETE ENDWALL CROSS DRAIN	T-WZ-51	04-02-12	TRAFFIC CONTROL FOR SIGNALS ONLY PROJECTS ON 4 OR 5 LANE MAJOR ROUTES
D-PG-3	04-15-97	FERROUS AND ALUMINUM CORRUGATED METAL PIPE	EROSION PREVENTION AND SEDIMENT CONTROL		
D-PS-1	03-15-76	STRUTTING DETAILS FOR COOR. METAL & STRUCTURAL PLATE ROUND PIPE	EC-STR-3D	04-01-08	ENHANCED SILT FENCE
DRAINAGE – CATCH BASINS AND MANHOLES					
D-JBS-1	08-01-12	STANDARD 32"X32" SQUARE CONCRETE NO. 1 JUNCTION BOX	EC-STR-3E	04-01-08	SILT FENCE FABRIC JOINING DETAILS
ROADSIDE SAFETY DEVICES AND FENCES					
S-CZ-1		CLEAR ZONE CRITERIA	EC-STR-6	08-01-12	ROCK CHECK DAM
TRAFFIC CONTROL APPURTENANCES					
T-M-1	11-01-11	DETAILS OF PAVEMENT MARKINGS FOR CONVENTIONAL ROADS AND MARKING ABBREVIATIONS	EC-STR-8	08-01-12	FILTER SOCK
T-M-4	11-01-11	STANDARD INTERSECTION PAVEMENT MARKINGS	EC-STR-19	04-01-08	CATCH BASIN PROTECTION
T-S-10	04-04-12	MOUNTING DETAILS - FLAT SHEET SIGNS, ALUMINUM-STEEL DESIGN			
T-S-16	11-01-11	GROUND MOUNTED ROADSIDE SIGN AND DETAILS			
T-S-17	07-19-13	STANDARD GROUND MOUNTED SIGN USING PERFORATED/KNOCKOUT SQUARE TUBE			
T-S-19	07-19-13	STANDARD MEMBERS BENDAWAY SIGN SUPPORTS STEEL DESIGN			

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HSIP-10(50)	1A

**UNOFFICIAL
SET
NOT FOR
BIDDING**

**INDEX
AND
STANDARD
DRAWINGS**

ESTIMATED ROADWAY QUANTITIES

ITEM NO.	DESCRIPTION	UNIT	QUANTITY
105-01	CONSTRUCTION STAKES, LINES AND GRADES	LS	1
201-01	CLEARING AND GRUBBING	LS	1
203-01	ROAD & DRAINAGE EXCAVATION (UNCLASSIFIED)	C.Y.	60
203-06	WATER	M.G.	1
202-02.01	REMOVAL OF PIPE (18" CMP, STA.99+51.07 TO STA. 99+55.07)	L.F.	4
(17) 202-03.01	REMOVAL OF ASPHALT PAVEMENT	S.Y.	5
(1) 209-03.22	FILTER SOCK (18 INCH)	L.F.	1650
209-05	SEDIMENT REMOVAL	C.Y.	200
(1) 209-08.04	TEMPORARY ENHANCED SILT FENCE	L.F.	60
(1) 209-08.07	ROCK CHECK DAM	EACH	9
(1) 209-40.33	CATCH BASIN PROTECTION (TYPE D)	EACH	2
303-01	MINERAL AGGREGATE, TYPE A BASE, GRADING D	TON	75
(1) 303-10.01	MINERAL AGGREGATE (SIZE 57)	TON	5
307-02.08	ASPHALT CONCRETE MIX (PG70-22) (BPMB-HM) GRADING B-M2	TON	6
402-01	BITUMINOUS MATERIAL FOR PRIME COAT (PC)	TON	1
402-02	AGGREGATE FOR COVER MATERIAL (PC)	TON	1
403-01	BITUMINOUS MATERIAL FOR TACK COAT (TC)	TON	1
(15) 411-01.10	ACS MIX(PG64-22) GRADING D	TON	10
(15) 604-01.01	CLASS A CONCRETE (ROADWAY)	C.Y.	45
607-03.02	18" CONCRETE PIPE CULVERT (CLASS III)	L.F.	20
611-02.10	JUNCTION BOX, TYPE 1	EACH	1
611-07.54	18 IN ENDWALL (CROSS DRAIN) 3:1	EACH	1
(1) 709-05.06	MACHINED RIP-RAP (CLASS A-1)	TON	23
712-01	TRAFFIC CONTROL	LS	1
712-04.01	FLEXIBLE DRUMS (CHANNELIZING)	EACH	20
712-06	SIGNS (CONSTRUCTION)	S.F.	263
712-08.03	ARROW BOARD (TYPE C)	EACH	1
712-09.01	REMOVABLE PAVEMENT MARKING LINE	L.F.	500
712-09.04	REMOVABLE PAVEMENT MARKING (STOP LINE)	L.F.	22
712-09.30	REMOVABLE BLACK-OUT TAPE (6")	L.F.	500
(2) 713-15	REMOVAL OF SIGNS, POSTS AND FOOTINGS	LS	1
(3)(10) 713-15.07	SUSPENDED FLAT SHEET ALUMINUM SIGN (0.080" THICK)	EACH	2
(16) 713-16.01	CHANGEABLE MESSAGE SIGN UNIT	EACH	1
(4) 713-16.21	SIGNS (W3-3, 36"x36")	EACH	5
(3) 713-16.22	SIGNS (STREET NAME SIGNS)	EACH	6
(5) 713-16.23	SIGNS (W3-4, 36"x36")	EACH	2
(5) 713-16.24	SIGNS (W16-13P, 24"x18")	EACH	2
(6) 716-02.05	PLASTIC PAVEMENT MARKING (STOP LINE)	L.F.	125
(6) 716-02.06	PLASTIC PAVEMENT MARKING (TURN LANE ARROW)	EACH	2
716-08.01	REMOVAL OF PAVEMENT MARKING (LINE)	L.F.	50
716-08.05	REMOVAL OF PAVEMENT MARKING (STOP LINE)	L.F.	45
716-08.11	REMOVAL OF WORD PAVEMENT MARKING (STOP)	EACH	1
716-08.12	REMOVAL OF WORD PAVEMENT MARKING (STOP AHEAD)	EACH	1
716-13.01	SPRAY THERMO PVMT MRKNG (60 MIL)(4 IN LINE)	L.M.	1.5
717-01	MOBILIZATION	LS	1
730-01.02	REMOVAL OF SIGNAL EQUIPMENT	EACH	1
730-02.01	SIGNAL HEAD ASSEMBLY (110)	EACH	4
730-02.09	SIGNAL HEAD ASSEMBLY (130 WITH BACKPLATE)	EACH	8
730-02.17	SIGNAL HEAD ASSEMBLY (150 A2H WITH BACKPLATE)	EACH	2
730-03.21	INSTALL PULL BOX (TYPE B)	EACH	10
(7) 730-05.01	ELECTRICAL SERVICE CONNECTION	EACH	1
730-05.03	SERVICE CABLE (2 CONDUCTOR, # 6 AWG)	L.F.	200
730-08.03	SIGNAL CABLE - 7 CONDUCTOR	L.F.	2700
(11) 730-09.01	SPAN WIRE ASSEMBLY (48,000 LBS. MIN. BRK. STRENGTH)	L.F.	450
(12) 730-09.02	SPAN WIRE ASSEMBLY (23,000 LBS. MIN. BRK. STRENGTH)	L.F.	115
730-10.01	TETHER WIRE ASSEMBLY - 1/4" DIAMETER	L.F.	575
730-11.01	STEEL CONDUIT RISER ASSEMBLY	EACH	1
730-12.01	CONDUIT 1" DIAMETER (PVC)	L.F.	925
730-12.02	CONDUIT 2" DIAMETER (PVC)	L.F.	1100
730-12.03	CONDUIT 3" DIAMETER (PVC)	L.F.	50
730-13.03	VEHICLE DETECTOR (4 - CHANNEL, RACK MOUNT)	EACH	2
730-14.01	SHIELDED DETECTOR CABLE	L.F.	2750
730-14.02	SAW SLOT	L.F.	1025
730-14.03	LOOP WIRE	L.F.	2050
730-15.32	CABINET (EIGHT PHASE BASE MOUNTED)	EACH	1
730-16.02	EIGHT PHASE ACTUATED CONTROLLER	EACH	1
(9)(13) 730-23.01	STEEL STRAIN POLE (SIGNAL SUPPORT)	EACH	4
(14) 730-23.02	STEEL STRAIN POLE (ADVANCED OVERHEAD FLASHING ASSEMBLY SUPPORTS)	EACH	2
730-23.96	CANTILEVER SIGNAL SUPPORT (1 ARM @ 50")	EACH	1
(1) 740-10.03	GEOTEXTILE (TYPE III)	S.Y.	54
(8) 801-01	SEEDING (WITH MULCH)	UNIT	1
801-03	WATER (SEEDING & SODDING)	M.G.	0.5
803-01	SOD (NEW SOD)	S.Y.	35

FOOTNOTES:

- (1) SEE SUBSECTION 209.07 OF THE STANDARD SPECIFICATIONS FOR MAINTENANCE REPLACEMENT.
- (2) INCLUDES THE REMOVAL OF EXISTING STOP SIGNS, STOP AHEAD WARNING SIGNS, STREET NAME SIGNS, AND INTERSECTION AHEAD WARNING SIGNS ONCE SIGNAL IS OPERATIONAL.
- (3) ITEM TO BE MOUNTED ON SPAN WIRE ASSEMBLY.
- (4) ONE (1) SIGN TO BE MOUNTED ON NORTHBOUND SPAN WIRE ASSEMBLY. ONE (1) SIGN TO BE MOUNTED ON SOUTHBOUND MAST ARM. THREE (3) SIGNS TO BE MOUNTED ON SIGN SUPPORT POST MEMBER DESIGNATION "P5". ITEM INCLUDES COST OF SIGN SUPPORT POST.
- (5) ITEMS TO BE MOUNTED ON SPAN WIRE ASSEMBLY OR MAST ARM. HARDWARE FOR ATTACHMENTS BETWEEN SIGNS TO BE INCLUDED IN PRICE.
- (6) THE CONTRACTOR MAY ELECT TO SUBSTITUTE PREFORMED PLASTIC FOR THE THERMOPLASTIC. PREFORMED PLASTIC SHALL BE PAID FOR AT THE SAME UNIT PRICE AS BID FOR THERMOPLASTIC.
- (7) THE CONTRACTOR WILL BE RESPONSIBLE FOR CONTACTING THE LOCAL UTILITY TO OBTAIN THE ESTIMATE FOR ANY CHANGES BY THE UTILITY FOR PROVIDING ELECTRICAL SERVICE TO THE CONTROLLER. THESE CHARGES SHALL BE INCLUDED IN THE PRICE FOR ITEM NO. 730-05.01 FOR PAYMENT BY THE CONTRACTOR. ITEM TO INCLUDE 1-2C #6 CABLE FROM EXISTING ELECTRIC SERVICE TO CONTROLLER. INCLUDES A 50 AMP, 2 POLE WEATHER PROOF EXTERNAL DISCONNECT. ENCLOSURE SHALL BE METALLIC WITH A 50 AMP SINGLE POLE CIRCUIT BREAKER.
- (8) ITEM TO BE USED FOR SIGNAL INSTALLATION EPSC.
- (9) ITEM INCLUDES POLE, BASE, FOUNDATION, AND ALL INCIDENTAL MATERIALS AND EQUIPMENT.
- (10) SIGNS TO BE R10-12, 30"x36".
- (11) ITEM INCLUDES SPAN WIRE ASSEMBLY FOR SIGNAL.
- (12) ITEM INCLUDES SPAN WIRE ASSEMBLY FOR NORTHBOUND ADVANCED OVERHEAD FLASHER ASSEMBLY.
- (13) ITEM INCLUDES STEEL STRAIN POLES FOR SIGNAL SUPPORTS WITH 504,500 FT-LBS CAPACITY.
- (14) ITEM INCLUDES STEEL STRAIN POLES FOR OVERHEAD ADVANCED FLASHING ASSEMBLY WITH 232,215 FT-LBS CAPACITY.
- (15) INCLUDES QUANTITY FOR CONDUIT PATCHING.
- (16) TO BE USED AS NEEDED FOR TRAFFIC CONTROL.
- (17) ITEM TO INCLUDE SAW CUTTING OF ASPHALT PAVEMENT.

SUMMARY OF QUANTITIES - ITEM NO. 712-06

SIGN NO.	DESCRIPTION	SIZE (IN.)	NUMBER REQUIRED
G20-2A	END ROAD WORK	48X24	4
W4-2R	LANE ENDS	48X48	1
W5-1	ROAD NARROWS	48X48	1
W8-9A	LOW SHOULDER	36X36	2
W8-11	UNEVEN LANES	36X36	2
W16-2P	500 FT SUPPLEMENTAL PLAQUE	24X18	1
W20-1	ROAD WORK 1/2 MILE	48X48	3
W20-1	ROAD WORK 1500 FEET	48X48	2
W20-1	ROAD WORK 1000 FEET	48X48	2
W20-1	ROAD WORK 500 FEET	48X48	1
W20-1	ROAD WORK AHEAD	48X48	1
W20-5R	RIGHT LANE CLOSED 1000 FEET	48X48	1

NOTES:

- (1) ITEM 712-06, SIGNS (CONSTRUCTION), INCLUDES SIGNS SHOWN AND IS CONSIDERED A MINIMUM. ADDITIONAL SIGNS MAY BE REQUIRED BY THE ENGINEER AND WILL BE PAID FOR AT THE PRICE BID FOR ITEM 712-06.
- (2) SIGNS SHALL BE LOCATED BY THE CONTRACTOR WITH THE APPROVAL OF THE ENGINEER.
- (3) CONSTRUCTION SIGNING AND TRAFFIC CONTROL SHALL CONFORM TO PART VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES AND SECTION 712 OF THE TENNESSEE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
- (4) THE CONTRACTOR IS NOT RELIEVED OF ANY RESPONSIBILITY TO PROVIDE ADEQUATE AND SAFE TRAFFIC CONTROL MEASURES BY THE ABOVE.

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HSIP-10(50)	2


REV. 7-14-14: ADDED ITEM NO. 713-16.01. DELETED ITEM NO. 725-03.84.

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION


**ESTIMATED
ROADWAY
QUANTITIES**

TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	2
CONST.	2014	HSIP-10(50)	2A



TANGENT SECTION
S.R. 10 (HUNTSVILLE HIGHWAY) STA. 99+17.46 TO STA. 99+77.19
(BASED ON STD. DWG. RD01-TS-3C)

SEE STD. DWG. RD01-S-11A FOR DITCH ROUNDING
SEE STD. DWG. RD01-S-11 FOR ROUNDING



TANGENT SECTION
S.R. 275 (LINCOLN ROAD) STA. 30+37.92 TO STA. 30+93.59
(BASED ON STD. DWG. RD01-TS-2)

PROPOSED PAVEMENT SCHEDULE

<p>① MINERAL AGGREGATE BASE¹ ITEM NO. 303-01 MINERAL AGGREGATE, TYPE A BASE, GRADING D ROADWAY @ 15.00" THICK</p>	<p>④ PRIME COAT ITEM NO. 402-01 BITUMINOUS MATERIAL FOR PRIME COAT (PC) @ 0.30 - 0.35 GAL./S.Y. ITEM NO. 402-02 AGGREGATE FOR COVER MATERIAL (PC) @ 8 - 12 LBS./S.Y.</p>
<p>② BITUMINOUS BINDER @ 2.00" THICK (APPROX. 226 LBS./S.Y.) ITEM NO. 307-02.08 ASPHALT CONCRETE MIX (PG70-22) (BPMB-HM) GRADING B-M2</p>	<p>⑤ TACK COAT ITEM NO. 403-01 BITUMINOUS MATERIAL FOR TACK COAT (TC) ITEM NO. 403-02 ASPHALT CEMENT FOR TACK COAT (TC)</p>
<p>③ BITUMINOUS SURFACE @ 1.25" THICK (APPROX. 132.5 LBS./S.Y.) ITEM NO. 411-02.10 ACS MIX (PG70-22) GRADING D</p>	

¹ THE MINERAL AGGREGATE BASE WILL BE PLACED AT A VARIABLE DEPTH AS NEEDED.

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

**TYPICAL
SECTIONS
AND
PAVEMENT
SCHEDULE**

GENERAL NOTES

GRADING

- (1) ANY AREA THAT IS DISTURBED OUTSIDE LIMITS OF CONSTRUCTION DURING THE LIFE OF THIS PROJECT SHALL BE REPAIRED BY THE CONTRACTOR AT HIS EXPENSE.
- (2) THE CONTRACTOR SHALL NOT DISPOSE OF ANY MATERIAL EITHER ON OR OFF STATE OR CITY-OWNED R.O.W. IN A REGULATORY FLOOD WAY AS DEFINED BY THE FEDERAL EMERGENCY MANAGEMENT AGENCY WITHOUT APPROVAL BY SAME. ALL MATERIAL SHALL BE DISPOSED OF IN UPLAND (NON-WETLAND) AREAS AND ABOVE ORDINARY HIGH WATER OF ANY ADJACENT WATER COURSE. THIS DOES NOT ELIMINATE THE NEED TO OBTAIN ANY OTHER LICENSES OR PERMITS THAT MAY BE REQUIRED BY ANY OTHER FEDERAL, STATE OR LOCAL AGENCY.

SEEDING AND SODDING

- (3) SOD SHALL BE PLACED AT LOCATIONS SHOWN ON THE PLANS TO PREVENT DAMAGE TO ADJACENT FACILITIES AND PROPERTY DUE TO EROSION ON ALL NEWLY GRADED CUT AND FILL SLOPES AS WORK PROGRESSES.
- (4) ITEM NO. 801-01, SEEDING (WITH MULCH), SHALL BE USED WHERE EROSION CONTROL BLANKET OR SOD ARE NOT APPLIED.

DRAINAGE

- (5) THE CONTRACTOR SHALL SHAPE DITCHES TO THE SPECIFIED DESIGN. THIS WORK WILL NOT BE MEASURED AND PAID FOR DIRECTLY, BUT THE COST WILL BE INCLUDED IN THE COST OF OTHER ITEMS.
- (6) EXCAVATION FOR DRAINAGE STRUCTURES WILL NOT BE MEASURED AND PAID FOR DIRECTLY, BUT WILL BE INCLUDED IN THE PRICE BID PER LINEAR FOOT OF PIPE (PIPE CULVERTS, STORM SEWERS, CONDUITS, ALL OTHER CULVERTS AND MINOR STRUCTURES).
- (7) THE CUTTING OF INLET AND OULET DITCHES WHERE SHOWN ON PLANS OR AS DIRECTED BY THE ENGINEER WILL BE MEASURED AND PAID FOR AS ITEM NO. 203-01 ROAD AND DRAINAGE EXCAVATION (UNCLASSIFIED).
- (8) WHERE A CULVERT (PIPE, SLAB OR BOX) IS MOVED TO A NEW LOCATION OTHER THAN THAT SHOWN ON THE PLANS, INCREASING OR DECREASING THE AMOUNT OF CULVERT EXCAVATION, NO INCREASE OR DECREASE IN THE AMOUNT OF PAYMENT WILL BE MADE DUE TO SUCH CHANGE.
- (9) DURING CONSTRUCTION OF DRAINAGE STRUCTURES ALL COST ASSOCIATED WITH MAINTAINING THE FLOW OF WATER AND TRAFFIC, AT THE STRUCTURES, DURING THE PHASED CONSTRUCTION OF THIS PROJECT ARE TO BE INCLUDED IN THE UNIT PRICE OF THE DRAINAGE STRUCTURES AND TRAFFIC CONTROL ITEMS.

UTILITIES

- (10) THE LOCATIONS OF UTILITIES SHOWN WITHIN THESE PLANS ARE APPROXIMATE ONLY. EXACT LOCATIONS SHALL BE DETERMINED IN THE FIELD BY CONTACTING THE UTILITY COMPANIES INVOLVED. NOTIFICATION BY CALLING THE TENNESSEE ONE CALL SYSTEM, INC., AT 1-800-351-1111 AS REQUIRED BY TCA 65-31-106 WILL BE REQUIRED.
- (11) UNLESS OTHERWISE NOTED, ALL UTILITY ADJUSTMENTS WILL BE PERFORMED BY THE UTILITY OR ITS REPRESENTATIVE. THE CONTRACTOR AND UTILITY OWNERS WILL BE REQUIRED TO COOPERATE WITH EACH OTHER IN ORDER TO EXPEDITE THE WORK REQUIRED BY THIS CONTRACT. ON CONTRACTS WHERE CONSTRUCTION STAKES, LINES, AND GRADES ARE CONTRACT ITEMS, THE CONTRACTOR WILL BE REQUIRED TO PROVIDE RIGHT-OF-WAY OR SLOPE STAKES, DITCH OR STREAM BED GRADES, OR OTHER ESSENTIAL SURVEY STAKING TO PREVENT CONFLICTS WITH THE HIGHWAY CONSTRUCTION. FREQUENTLY, THIS WILL BE REQUIRED AS THE FIRST ITEM OF WORK AND AT ANY LOCATION ON THE PROJECT DIRECTED BY THE ENGINEER.
- (12) THE CONTRACTOR WILL PROVIDE ALL NECESSARY PROTECTIVE MEASURES TO SAFEGUARD EXISTING UTILITIES FROM DAMAGE DURING CONSTRUCTION OF THIS PROJECT. IN THE EVENT THAT SPECIAL EQUIPMENT IS REQUIRED TO WORK OVER AND AROUND THE UTILITIES, THE CONTRACTOR WILL BE REQUIRED TO FURNISH SUCH EQUIPMENT. THE COST OF PROTECTING UTILITIES FROM DAMAGE AND FURNISHING SPECIAL EQUIPMENT WILL BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS OF CONSTRUCTION.
- (13) PRIOR TO SUBMITTING HIS BID, THE CONTRACTOR WILL BE SOLELY RESPONSIBLE FOR CONTACTING OWNERS OF ALL AFFECTED UTILITIES IN ORDER TO DETERMINE THE EXTENT TO WHICH UTILITY RELOCATIONS

AND/OR ADJUSTMENTS WILL HAVE UPON THE SCHEDULE OF WORK FOR THE PROJECT. WHILE SOME WORK MAY BE REQUIRED 'AROUND' UTILITY FACILITIES THAT WILL REMAIN IN PLACE, OTHER UTILITY FACILITIES MAY NEED TO BE ADJUSTED CONCURRENTLY WITH THE CONTRACTOR'S OPERATIONS. ADVANCE CLEAR CUTTING MAY BE REQUIRED BY THE ENGINEER AT ANY LOCATION WHERE CLEARING IS CALLED FOR IN THE SPECIFICATIONS AND CLEAR CUTTING IS NECESSARY FOR A UTILITY RELOCATION. ANY ADDITIONAL COST WILL BE INCLUDED IN THE UNIT PRICE BID FOR THE CLEARING ITEM SPECIFIED IN THE PLANS.

- (14) THE CONTRACTOR SHALL NOTIFY EACH INDIVIDUAL UTILITY OWNER OF HIS PLAN OF OPERATION IN THE AREA OF THE UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL CONTACT THE UTILITY OWNERS AND REQUEST THEM TO PROPERLY LOCATE THEIR RESPECTIVE UTILITY ON THE GROUND. THIS NOTIFICATION SHALL BE GIVEN AT LEAST THREE (3) BUSINESS DAYS PRIOR TO COMMENCEMENT OF OPERATIONS AROUND THE UTILITY IN ACCORDANCE WITH TCA 65-31-106.

SIGNING

- (15) THE TOP OF THE SIGN FOOTINGS SHALL BE PLACED LEVEL WITH THE GROUND LINE.
- (16) ALL SIGNS MARKED "TO BE REMOVED" ARE TO BE REMOVED BY THE CONTRACTOR AND PAID FOR UNDER ITEM 713-15 AND BECOME THE PROPERTY OF THE CONTRACTOR.
- (17) THE EXISTING FOOTINGS ARE TO BE REMOVED 6 INCHES BELOW GROUND LINE.
- (18) THE LETTERS, DIGITS, ARROWS, BORDERS, AND ALPHABET ACCESSORIES ON ALL FLAT SHEET SIGNS SHALL BE APPLIED BY SILK SCREENING PROCESS.

SIGNALIZATION

- (19) EQUIPMENT AND INSTALLATION OF TRAFFIC SIGNALS SHALL COMPLY WITH TDOT STANDARD SPECIFICATIONS, SECTION 730.
- (20) SALVAGEABLE EQUIPMENT SHALL BECOME THE PROPERTY OF THE COUNTY AND SHALL BE STOCKPILED AT A LOCATION DESIGNATED BY THE ENGINEER FOR BY THE COUNTY.
- (21) ANY SIGNAL HEADS, WHEN VISIBLE TO DRIVERS BUT NOT OPERATIONAL, SHALL BE COMPLETELY COVERED.
- (22) SIGNAL HEADS SHALL FLASH A MINIMUM OF SEVEN (7) DAYS PRIOR TO ACTIVATION OF THE SIGNAL.

MISCELLANEOUS

- (23) NOTHING IN THE GENERAL NOTES OR SPECIAL PROVISIONS SHALL RELIEVE THE CONTRACTOR FROM HIS RESPONSIBILITIES TOWARD THE SAFETY AND CONVENIENCE OF THE GENERAL PUBLIC AND RESIDENTS ALONG THE PROPOSED CONSTRUCTION AREA.

PAVEMENT MARKINGS

- (24) PERMANENT PAVEMENT LINE MARKINGS SHALL BE 4" SPRAY THERMOPLASTIC (60 MIL) INSTALLED TO PERMANENT STANDARDS AT THE END OF EACH DAY'S WORK. SHORT UNMARKED SECTIONS SHALL NOT BE ALLOWED. PAVEMENT MARKINGS WILL BE MEASURED AND PAID FOR UNDER ITEM NO. 716-13.01, SPRAY THERMO PVMT MRKNG (60MIL) (4 IN LINE), L.M. THE CONTRACTOR SHALL HAVE THE OPTION OF USING REFLECTORIZED PAINT INSTALLED TO PERMANENT STANDARDS AT THE END OF EACH DAY'S WORK AND THEN INSTALLING THE PERMANENT MARKINGS AFTER THE PAVING OPERATION IS COMPLETED. THE TEMPORARY MARKINGS FOR THE FINAL SURFACE WILL NOT BE MEASURED AND PAID FOR DIRECTLY, BUT THE COSTS ARE TO BE INCLUDED IN THE PRICE BID FOR THE PERMANENT MARKINGS.
- (25) THE PAVEMENT MARKING ON THE LANE SHIFT FOR LANE LINES WILL BE INSTALLED AND MAINTAINED TO THE SAME STANDARDS AS FOR PERMANENT MARKINGS ON THE MAIN ROADWAY. THESE MARKINGS SHALL BE IN PLACE PRIOR TO ALLOWING TRAFFIC ONTO THE PAVEMENT. THESE PAVEMENT MARKINGS WILL BE MEASURED AND PAID FOR UNDER ITEM NO. 712-09.01 REMOVABLE PAVEMENT MARKING LINE, LIN. FT.
- (26) BEFORE OPENING THE LANE SHIFT TO TRAFFIC, THE TRANSITIONAL MARKINGS ON THE EXISTING ROADWAY MUST BE IN PLACE. THESE MARKINGS WILL BE MEASURED AND PAID FOR UNDER ITEM 712-09.01 REMOVABLE PAVEMENT MARKING LINE, LIN. FT. ALL EXISTING MARKINGS IN THE AREA OF THESE TRANSITIONAL MARKINGS SHALL BE OBLITERATED AND ALL EXISTING RAISED PAVEMENT MARKERS SHALL BE REMOVED TO ELIMINATE CONFLICTING MARKINGS. REMOVAL OF THE EXISTING CONFLICTING MARKINGS AND RAISED PAVEMENT MARKERS

WILL NOT BE MEASURED AND PAID FOR DIRECTLY, BUT THE COST WILL BE INCLUDED IN ITEM NO. 712-01 TRAFFIC CONTROL, LUMP SUM.

- (27) BEFORE OPENING THE LANE SHIFT TO TRAFFIC, THE TRANSITIONAL MARKINGS ON THE EXISTING ROADWAY MUST BE IN PLACE. ALL EXISTING MARKINGS IN THE AREA OF THESE TRANSITIONAL MARKINGS SHALL BE OBLITERATED AND ALL EXISTING RAISED PAVEMENT MARKERS SHALL BE REMOVED TO ELIMINATE CONFLICTING MARKINGS. REMOVAL OF THE EXISTING CONFLICTING MARKINGS AND RAISED PAVEMENT MARKERS WILL NOT BE MEASURED AND PAID FOR DIRECTLY, BUT THE COST WILL BE INCLUDED IN ITEM NO. 712-01 TRAFFIC CONTROL, LUMP SUM.

PAVING

- (28) THE CONTRACTOR SHALL BE REQUIRED TO PAVE IN THE DIRECTION OF TRAFFIC.
- (29) THE CONTRACTOR SHALL ATTACH A DEVICE TO THE SCREED OF THE PAVER SUCH THAT MATERIAL IS CONFINED AT THE END GATE AND EXTRUDES THE ASPHALT MATERIAL IN SUCH A WAY THAT RESULTS IN A CONSOLIDATED WEDGE-SHAPE PAVEMENT EDGE OF APPROXIMATELY 25 TO 30 DEGREES AS IT LEAVES THE PAVER (MEASURED FROM A LINE PARALLEL TO THE PAVEMENT SURFACE.) THE DEVICE SHALL MEET THE REQUIREMENTS THAT ARE CURRENTLY SET FORTH IN SPECIAL PROVISION 407SE.
- (30) WHERE DIRECTED BY THE TDOT ENGINEER, THE CONTRACTOR SHALL BE REQUIRED TO SHAPE PUBLIC SIDE ROADS, BUSINESS ENTRANCES, AND PRIVATE DRIVES, AS WELL AS CLEANING OF EXISTING DRAINS BEFORE PLACING MATERIALS. ALL COSTS ARE TO BE INCLUDED IN THE PRICE BID FOR OTHER ITEMS OF CONSTRUCTION.
- (31) IN ALL CASES THE LENGTH OF THE PAVEMENT TRANSITION, THE THICKNESS AND WIDTH OF THE RESURFACING AND ANY ADDITIONAL PAVEMENT MATERIALS SHALL BE AS DIRECTED BY THE TDOT ENGINEER.

CONSTRUCTION WORK ZONE & TRAFFIC CONTROL NOTES

- (32) ADVANCED WARNING SIGNS SHALL NOT BE DISPLAYED MORE THAN FORTY-EIGHT (48) HOURS BEFORE PHYSICAL CONSTRUCTION BEGINS. SIGNS MAY BE ERECTED UP TO ONE WEEK BEFORE NEEDED, IF THE SIGN FACE IS FULLY COVERED.
- (33) IF THE CONTRACTOR MOVES OFF THE PROJECT, HE SHALL COVER OR REMOVE ALL UNNEEDED SIGNS AS DIRECTED BY THE ENGINEER. COSTS OF REMOVAL, COVERING, AND REINSTALLING SIGNS SHALL NOT BE MEASURED AND PAID FOR SEPARATELY, BUT ALL COSTS SHALL BE INCLUDED IN THE ORIGINAL UNIT PRICE BID FOR ITEM NO 712-06, SIGNS (CONSTRUCTION) PER SQUARE FOOT.
- (34) A LONG TERM BUT SPORADIC USE WARNING SIGN, SUCH AS A FLAGGER SIGN, MAY REMAIN IN PLACE WHEN NOT REQUIRED PROVIDED THE SIGN FACE IS FULLY COVERED.
- (35) TRAFFIC CONTROL DEVICES SHALL NOT BE DISPLAYED OR ERECTED UNLESS RELATED CONDITIONS ARE PRESENT NECESSITATING WARNING.
- (36) USE OF BARRICADES, PORTABLE BARRIER RAILS, VERTICAL PANELS, AND DRUMS SHALL BE LIMITED TO THE IMMEDIATE AREAS OF CONSTRUCTION WHERE A HAZARD IS PRESENT. THESE DEVICES SHALL NOT BE STORED ALONG THE ROADWAY WITHIN THIRTY (30) FEET OF THE EDGE OF THE TRAVELED WAY BEFORE OR AFTER USE UNLESS PROTECTED BY GUARDRAIL, BRIDGE RAIL, AND/OR BARRIERS INSTALLED FOR OTHER PURPOSES FOR ROADWAYS WITH CURRENT ADT'S LESS THAN 1500 AND DESIGN SPEED OF LESS THAN 60 MPH. THIS DISTANCE SHALL INCREASE TO FORTY-FIVE (45) FEET FOR ROADWAYS WITH CURRENT ADT'S OF 1500 OR GREATER AND DESIGN SPEED OF 60 MPH OR GREATER OR ON THE OUTSIDE OF A HORIZONTAL CURVE. THESE DEVICES SHALL BE REMOVED FROM THE CONSTRUCTION WORK ZONE WHEN THE ENGINEER DETERMINES THEY ARE NO LONGER NEEDED. WHERE THERE IS INSUFFICIENT RIGHT-OF-WAY TO PROVIDE FOR THIS REQUIRED SETBACK, THE CONTRACTOR SHALL DETERMINE THE ALTERNATE LOCATIONS AND REQUEST THE ENGINEER'S APPROVAL TO USE THEM.

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HSIP-10(50)	2B

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

**GENERAL NOTES
AND
SPECIAL NOTES**

GENERAL NOTES (CONT'D)

- (1) THE CONTRACTOR SHALL NOT BE PERMITTED TO PARK ANY VEHICLES OR CONSTRUCTION EQUIPMENT DURING PERIODS OF INACTIVITY, WITHIN THIRTY (30) FEET OF THE EDGE OF PAVEMENT WHEN THE LANE IS OPEN TO TRAFFIC UNLESS PROTECTED BY GUARDRAIL, BRIDGE RAIL, AND/OR BARRIERS INSTALLED FOR OTHER PURPOSES FOR ROADWAYS WITH CURRENT ADT'S LESS THAN 1500 AND DESIGN SPEED OF LESS THAN 60 MPH. THIS DISTANCE SHALL BE INCREASED TO FORTY-FIVE (45) FEET FOR ROADWAYS WITH CURRENT ADT'S OF 1500 OR GREATER AND DESIGN SPEED OF 60 MPH OR GREATER OR ON THE OUTSIDE OF A HORIZONTAL CURVE. PRIVATELY OWNED VEHICLES SHALL NOT BE ALLOWED TO PARK WITHIN THIRTY (30) FEET OF AN OPEN TRAFFIC LANE AT ANY TIME UNLESS PROTECTED AS DESCRIBED ABOVE FOR ROADWAYS WITH CURRENT ADT'S LESS THAN 1500 AND DESIGN SPEED OF LESS THAN 60 MPH. THIS DISTANCE SHALL BE INCREASED TO FORTY-FIVE (45) FEET FOR ROADWAYS WITH CURRENT ADT'S OF 1500 OR GREATER AND DESIGN SPEED OF 60 MPH OR GREATER OR ON THE OUTSIDE OF A HORIZONTAL CURVE. WHERE THERE IS INSUFFICIENT RIGHT-OF-WAY TO PROVIDE FOR THIS REQUIRED SETBACK, THE CONTRACTOR SHALL DETERMINE THE ALTERNATE LOCATIONS AND REQUEST THE ENGINEER'S APPROVAL TO USE THEM.

- (2) ALL DETOUR AND CONSTRUCTION SIGNING SHALL BE IN STRICT ACCORDANCE WITH THE CURRENT EDITION OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

EROSION PREVENTION AND SEDIMENT CONTROL

- (3) AREAS TO BE UNDISTURBED SHALL BE CLEARLY MARKED IN THE FIELD BEFORE CONSTRUCTION ACTIVITIES BEGIN.
- (4) PRE-CONSTRUCTION VEGETATIVE GROUND COVER SHALL NOT BE DESTROYED, REMOVED OR DISTURBED (I.E. CLEARING AND GRUBBING INITIATED) MORE THAN 15 CALENDAR DAYS PRIOR TO GRADING OR EARTH MOVING ACTIVITIES UNLESS THE AREA IS MULCHED, SEEDED WITH MULCH, OR OTHER TEMPORARY COVER IS INSTALLED.
- (5) CLEARING, GRUBBING, AND OTHER DISTURBANCE TO RIPARIAN VEGETATION SHALL BE LIMITED TO THE MINIMUM NECESSARY FOR SLOPE CONSTRUCTION AND EQUIPMENT OPERATIONS. UNNECESSARY VEGETATION REMOVAL IS PROHIBITED.
- (6) ALL DISTURBED AREAS SHALL BE PROPERLY STABILIZED AS SOON AS PRACTICABLE. PRIORITY SHALL BE GIVEN TO FINISHING OPERATIONS AND PERMANENT EPSC MEASURES OVER TEMPORARY EPSC MEASURES ON ALL PROJECTS.
- (7) CONSTRUCTION SHALL BE SEQUENCED AND STAGED TO MINIMIZE THE EXPOSURE TIME OF GRADED OR DENUDED SOIL AREAS, PRESERVE TOPSOIL, AND MINIMIZE SOIL COMPACTION.
- (8) EPSC MEASURES SHALL BE INSTALLED CONCURRENTLY WITH CLEARING OPERATIONS, SHALL BE FUNCTIONAL PRIOR TO ANY EARTH MOVING OPERATIONS, AND SHALL BE MAINTAINED THROUGHOUT THE CONSTRUCTION PERIOD.
- (9) THE CONTRACTOR SHALL ESTABLISH AND MAINTAIN A PROACTIVE METHOD TO PREVENT THE OFF-SITE MIGRATION OR DEPOSIT OF SEDIMENT ON ROADWAYS USED BY THE GENERAL PUBLIC. IF SEDIMENT ESCAPES THE CONSTRUCTION SITE, OFF-SITE ACCUMULATIONS OF SEDIMENT THAT HAVE NOT REACHED A STREAM MUST BE REMOVED AT A FREQUENCY SUFFICIENT TO MINIMIZE OFF-SITE IMPACTS (E.G., FUGITIVE SEDIMENT THAT HAS ESCAPED THE CONSTRUCTION SITE AND HAS COLLECTED IN A STREET MUST BE REMOVED SO THAT IT IS NOT SUBSEQUENTLY WASHED INTO STORM SEWERS AND STREAMS BY THE NEXT RAIN AND/OR SO THAT IT DOES NOT POSE A SAFETY HAZARD TO USERS OF PUBLIC STREETS). ARRANGEMENTS CONCERNING REMOVAL OF SEDIMENT ON ADJOINING PROPERTY MUST BE SETTLED WITH THE ADJOINING PROPERTY OWNER BEFORE REMOVAL OF SEDIMENT.
- (10) CHECK DAMS SHALL BE USED WHERE RUNOFF IS CONCENTRATED. CLEAN ROCK, BRUSH, GABION, OR SANDBAG CHECK DAMS SHALL BE PROPERLY CONSTRUCTED TO REDUCE VELOCITY AND CONTROL EROSION.
- (11) TEMPORARY EPSC MEASURES MAY BE REMOVED AT THE BEGINNING OF THE WORKDAY, BUT MUST BE REPLACED AT THE END OF THE WORKDAY.
- (12) EPSC CONTROLS WILL BE MAINTAINED IN ACCORDANCE WITH TDOT STANDARD DRAWINGS AND GOOD ENGINEERING PRACTICES.
- (13) INSPECTION, REPAIR, AND MAINTENANCE OF EPSC MEASURES/STRUCTURES IS TO BE PERFORMED ON A REGULAR BASIS.

SEDIMENT SHALL BE REMOVED FROM SEDIMENT CONTROL STRUCTURES WHEN THE DESIGN CAPACITY HAS BEEN REDUCED BY FIFTY PERCENT (50%), DURING SEDIMENT REMOVAL, THE CONTRACTOR SHALL TAKE CARE TO ENSURE THAT STRUCTURAL COMPONENTS OF EPSC MEASURES ARE NOT DAMAGED AND THUS MADE INEFFECTIVE. IF DAMAGE DOES OCCUR, THE CONTRACTOR SHALL REPAIR THE STRUCTURES AT THE CONTRACTOR'S OWN EXPENSE.

- (14) SEDIMENT REMOVED FROM SEDIMENT CONTROL STRUCTURES SHALL BE PLACED AND BE TREATED IN A MANNER SO THAT THE SEDIMENT IS CONTAINED WITHIN THE PROJECT LIMITS AND DOES NOT MIGRATE INTO WATERS OF THE STATE/U.S. COST FOR THIS TREATMENT IS TO BE INCLUDED IN PRICE BID FOR ITEM NO. 209-05 SEDIMENT REMOVAL, C.Y.
- (15) THE CONTRACTOR SHALL INSTALL A RAIN GAUGE EVERY LINEAR MILE AT ALL SITES WHERE CLEARING, GRUBBING, EXCAVATION, GRADING CUTTING OR FILLING IS BEING ACTIVELY PERFORMED, OR EXPOSED SOIL HAS NOT YET BEEN PERMANENTLY STABILIZED. IF THE PROJECT LENGTH IS LESS THAN ONE LINEAR MILE, ONE RAIN GAUGE SHALL BE INSTALLED AT THE CENTER OF THE PROJECT OR AS INDICATED BY THE TDOT EPSC INSPECTOR. THE CONTRACTOR SHALL ENSURE THAT EACH GAUGE IS MAINTAINED IN GOOD WORKING CONDITION. TDOT AND/OR THE CONTRACTOR SHALL RECORD DAILY PRECIPITATION AND FORECASTED PERCENTAGE OF PRECIPITATION IN DETAILED RECORDS OF RAINFALL EVENTS INCLUDING DATES, AMOUNTS OF RAINFALL PER GAUGE, THE ESTIMATED DURATION (OR STARTING AND ENDING TIMES), AND FORECASTED PERCENTAGE OF PRECIPITATION FOR THE PROJECT. THIS INFORMATION SHALL BE PROVIDED TO THE ENGINEER ON A MONTHLY BASIS. THE COST FOR THE RAIN GAUGES IS TO BE INCLUDED IN THE UNIT BID PRICES FOR OTHER ITEMS. RAIN GAUGES SHALL BE AS SPECIFIED IN THE APPROVED TDOT RAINFALL MONITORING PLAN.
- (16) INSPECTION OF EPSC MEASURES SHALL BE DONE AT LEAST TWICE PER CALENDAR WEEK AT LEAST 72 HOURS APART. A CALENDAR WEEK IS DEFINED AS SUNDAY THROUGH SATURDAY. QUALITY ASSURANCE/QUALITY CONTROL SITE ASSESSMENT OF EPSC SHALL BE PERFORMED PER THE TDOT ENVIRONMENTAL DIVISION'S COMPREHENSIVE INSPECTION OFFICE GUIDELINES.
- (17) OUTFALL POINTS SHALL BE INSPECTED TO ASCERTAIN WHETHER EPSC MEASURES ARE EFFECTIVE IN PREVENTING SIGNIFICANT IMPACTS TO SURROUNDING WATERS. WHERE DISCHARGE LOCATIONS ARE INACCESSIBLE, NEARBY DOWNSTREAM LOCATIONS SHALL BE INSPECTED. LOCATIONS WHERE VEHICLES ENTER AND EXIT THE SITE SHALL BE INSPECTED FOR EVIDENCE OF OFF-SITE ROADWAY SEDIMENT TRACKING.
- (18) UPON CONCLUSION OF THE INSPECTIONS, EPSC MEASURES FOUND TO BE INEFFECTIVE SHALL BE REPAIRED, REPLACED, OR MODIFIED BEFORE THE NEXT RAIN EVENT, IF POSSIBLE, BUT IN NO CASE MORE THAN 24 HOURS AFTER THE INSPECTION OR WHEN THE CONDITION IS IDENTIFIED. IF THE REPAIR, REPLACEMENT OR MODIFICATION IS NOT PRACTICAL WITHIN THE TIMEFRAME, WRITTEN DOCUMENTATION MUST BE PROVIDED IN THE FIELD BOOK AND AN ESTIMATED REPAIR, REPLACEMENT OR MODIFICATION SCHEDULE SHALL BE DOCUMENTED WITHIN 24 HOURS AFTER IDENTIFICATION.
- (19) THE TDOT PROJECT SUPERVISOR (OR THEIR DESIGNEE) AND THE CONTRACTOR'S SITE SUPERINTENDENT ARE RESPONSIBLE FOR INSPECTIONS. MAINTENANCE AND REPAIR ACTIVITIES ARE THE RESPONSIBILITY OF THE CONTRACTOR. THE TDOT PROJECT SUPERVISOR OR THEIR DESIGNEE WILL COMPLETE THE INSPECTION REPORTS AND DISTRIBUTE COPIES PER THE CONTRACT.

LITTER, DEBRIS, WASTE, PETROLEUM

- (20) THE CONTRACTOR SHALL ESTABLISH AND MAINTAIN A PROACTIVE METHOD TO PREVENT LITTER, CONSTRUCTION DEBRIS, AND CONSTRUCTION WASTES FROM ENTERING WATERS OF THE STATE/U.S. THESE MATERIALS WILL BE PICKED UP AND REMOVED FROM STORMWATER EXPOSURE PRIOR TO ANTICIPATED STORM EVENTS. AFTER USE, MATERIALS USED FOR EPSC WILL BE REMOVED FROM THE SITE.
- (21) THE CONTRACTOR SHALL TAKE APPROPRIATE STEPS TO ENSURE THAT PETROLEUM PRODUCTS OR OTHER CHEMICAL POLLUTANTS ARE PREVENTED FROM ENTERING WATERS OF THE STATE/U.S. ALL EQUIPMENT REFUELING, SERVICING, AND STAGING AREAS SHALL COMPLY WITH ALL LOCAL, STATE, AND FEDERAL LAWS, RULES, REGULATIONS, AND ORDINANCES, INCLUDING THOSE OF THE NATIONAL FIRE PROTECTION ASSOCIATION (NFPA). APPROPRIATE CONTAINMENT MEASURES FOR THESE AREAS SHALL BE USED. ALL SPILLS MUST BE REPORTED TO THE APPROPRIATE AGENCY, AND MEASURES SHALL BE TAKEN IMMEDIATELY TO PREVENT THE POLLUTION OF WATERS OF THE STATE/U.S., INCLUDING GROUNDWATER, SHOULD A SPILL OCCUR.

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HSIP-10(50)	2C

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

**GENERAL NOTES
AND
SPECIAL NOTES**

TENNESSEE D.O.T.
DESIGN DIVISION
FILE NO.

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HSIP-10(50)	2D

SPECIAL NOTES

TRAFFIC SIGNAL

- (1) ALL SIGNAL DISPLAYS AND CLEARANCES SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES, CURRENT EDITION.
- (2) LOCATIONS OF SIGNAL POLES ARE APPROXIMATE AND CAN BE ADJUSTED UP TO 2 FT. IN THE FIELD TO AVOID UTILITY CONFLICT. THE MAST ARM LENGTH SHOULD BE VERIFIED BASED ON THE FIELD LOCATION OF THE SIGNAL POLES.
- (3) LOCATIONS OF STEEL STRAIN SIGNAL POLES ARE APPROXIMATE AND CAN BE ADJUSTED UP TO 5 FT. IN THE FIELD TO AVOID UTILITY CONFLICT. THE SPAN WIRE LENGTHS SHOULD BE VERIFIED BASED ON THE FIELD LOCATION OF THE SIGNAL POLES.
- (4) ALL CIRCULAR AND ARROW INDICATIONS WITHIN ALL VEHICULAR SIGNAL HEADS PROPOSED FOR THIS PROJECT SHALL CONSIST OF AN LED (LIGHT EMITTING DIODE) SIGNAL MODULE UNLESS OTHERWISE NOTED IN THE PLANS.

CIRCULAR INDICATIONS SHALL MEET "ITE VTC SH-LED CIRCULAR SIGNAL SUPPLEMENT" FOR EXPANDED/EXTENDED VIEW.

ARROW INDICATIONS SHALL MEET "ITE VTC SH-LED ARROW SPECIFICATION" FOR EXPANDED/EXTENDED VIEW.

INCANDESCENT OR SCREW-IN MODULES ARE NOT ACCEPTABLE.

COMPATABILITY WITH CONFLICT MONITORS AND LOAD SWITCHES SHALL BE TESTED AND CONFIRMED.

MANUFACTURER SHALL PROVIDE A MINIMUM FIVE-YEAR WARRANTY FOR OPERATION OF THE LED UNIT.

- (5) THE DESIGN OF TRAFFIC SIGNAL SUPPORT POLES, MAST ARMS, STRAIN POLES, ETC. SHALL BE IN CONFORMANCE WITH THE *AASHTO STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINAIRES AND TRAFFIC SIGNALS*, CURRENT EDITION. OVERHEAD CANTILEVERED TRAFFIC SIGNAL STRUCTURES SHALL BE DESIGNED FOR FATIGUE CATEGORY 1.
- (6) SIGNAL HEADS SHALL INCLUDE LOUVERED BACKPLATES WITH A 1" MINIMUM YELLOW RETRO REFLECTIVE BORDER AROUND THE PERIMETER OF THE FACE OF THE BACKPLATE. THE RETRO REFLECTIVE BORDER TO BE MADE OF A TYPE III PRISMATIC OR BETTER MATERIAL.

SIGNAL EROSION PREVENTION AND SEDIMENT CONTROL

- (7) IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PROTECT FROM EROSION ANY EXPOSED EARTH RESULTING FROM TRENCHING AND EXCAVATION, AND TO PROVIDE FOR CONTAINMENT OF SEDIMENT THAT MAY RESULT FROM THIS WORK. PRIOR TO BEGINNING WORK, ADEQUATE MEASURES MUST BE IN PLACE TO TRAP ANY SEDIMENT THAT MAY TRAVEL OFF-SITE IN THE EVENT OF RAIN. DURING THE PROGRESSION OF THE WORK, EXPOSED EARTH AREAS SHALL BE STABILIZED AS SOON AS POSSIBLE TO PREVENT EROSION. AT NO TIME SHALL EXPOSED EARTH RESULTING FROM THESE OPERATIONS HAVE UNPROTECTED ACCESS TO FLOWING OFF-SITE AND ENTERING WATERS OF THE STATE/U.S.
- (8) SILT FENCE OR OTHER BARRIERS OF THE SPECIFIED TYPE SHALL BE INSTALLED ON THE DOWNHILL SIDE OF STOCKPILED SOIL. POLYETHYLENE SHEETING MAY BE USED TO COVER SPOILS FROM EXCAVATION. NO SEPARATE PAYMENT FOR POLYETHYLENE SHEETING.
- (9) TRENCHING ACROSS WET WEATHER CONVEYANCES SHALL BE DONE DURING NO FLOW CONDITIONS AND STABILIZED BY THE END OF THE WORK DAY.
- (10) THE CONTRACTOR SHALL RESTORE ALL AFFECTED WET WEATHER CONVEYANCES TO THE EXISTING TOPOGRAPHIC CONDITIONS (AS INDICATED BY THE APPROVED EROSION PREVENTION AND SEDIMENT CONTROL PLAN OR THE TDOT PROJECT ENGINEER).
- (11) FOR THE INSTALLATION OF CONDUITS AND CABLES, TRENCHES SHALL BE BACKFILLED DAILY AS CONSTRUCTION PROCEEDS. BACKFILLED TRENCHES SHALL BE SEEDED AND MULCHED OR SODDED DAILY IF POSSIBLE, BUT NO LATER THAN SEVEN DAYS AFTER BEING BACKFILLED, OR IMMEDIATELY AFTER ANY INSPECTION. ANY TEMPORARY SPOIL OF EXCAVATED EARTH SHALL BE LOCATED WITHIN TDOT EROSION PREVENTION AND SEDIMENT CONTROL MEASURES. IF TRENCHES ARE NOT BACKFILLED OVERNIGHT, APPROPRIATE EPSC MEASURES WILL BE

- INSTALLED BY THE CONTRACTOR UNTIL SUCH TIME AS THE TRENCH IS BACKFILLED.
- (12) RAIN WATER WHICH COLLECTS IN THE OPEN EXCAVATIONS (TRENCHES OR FOUNDATION EXCAVATIONS) SHALL BE PUMPED INTO A DEWATERING STRUCTURE OR SEDIMENT FILTER BAG AND MAINTAINED. NO SEPARATE PAYMENT FOR THIS REQUIREMENT.
- (13) SPOILS FROM FOUNDATION EXCAVATIONS SHALL BE PICKED UP AS BORING PROGRESSES, OR CONTAINED WITHIN APPROPRIATE EPSC MEASURES.

4/22/2014 8:33:16 AM C:\Users\RPW\Desktop\4-22-14\SR 10 Construction\Construction info\0020.sht

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION



**GENERAL NOTES
AND
SPECIAL NOTES**

- NOTES:
1. WATER VALVES, GAS VALVE, AND FIBER UTILITY LINE IN THE SOUTHEAST CORNER OF THE INTERSECTION MAY NEED TO BE ADJUSTED AND/OR RELOCATED TO ACCOMMODATE PROPOSED SHOULDER AND CULVERT EXTENSION. CONTRACTOR TO COORDINATE WITH UTILITIES.
2. PIPES AND DITCHES THAT ARE NOTED ON SURVEY AS FILLED WITH DEBRIS OR BURIED ARE TO BE CLEANED OUT AND RESTORED AS A PART OF THIS PROJECT.
3. THE CONTRACTOR SHALL TAKE APPROPRIATE STEPS, BEFORE CLEANING OUT OR REMOVAL/REPLACEMENT OF DITCHES, SIDE DRAINS, AND CROSS DRAINS, TO ENSURE THAT THE DRAINAGE FEATURES/WATERCOURSES ARE NOT STREAMS OR WETLANDS. IF THE CONTRACTOR/TDOT INSPECTOR IS UNSURE WHETHER THE DRAINAGE FEATURES ARE STREAMS OR WETLANDS, THE INSPECTOR SHALL CONTACT THE TDOT ENVIRONMENTAL DIVISION, PERMITS SECTION TO OBTAIN THE APPROPRIATE PERMITS.
- D1 TOP-914.11
 - D2 BOT-913.59
 - D3 OUT-913.52
 - D4 4" PVC
 - D5 INV-911.24
 - D6 BOT-909.40
 - D7 IN-909.68
 - D8 OUT-909.40
 - D9 INV-901.41
 - D10 INV-905.95
 - D11 INV-905.25
 - D12 INV-903.94
 - D13 INV-903.62
 - D14 INV-906.28
 - D15 W/STONE
 - D16 ENDWALL
 - D17 INV-905.76
 - D18 W/STONE
 - D19 ENDWALL
 - D20 INV-901.93
 - D21 INV-905.25
 - D22 INV-903.94
 - D23 INV-903.62
 - D24 INV-906.28
 - D25 W/STONE
 - D26 ENDWALL


95 BANK OF FRANKEWING
STEVE C. PEARSON AND WIFE, AVA J. PEARSON
BEGIN PROJ. NO. 52003-3216-94 (CONST)
STA. 99+17.46 (SR 10)
N 251715.0442
E 1796036.7742

CONTROL POINTS						
POINT	NORTH	EAST	ELEV.	STATION	OFFSET	DESCRIPTION
S1	251281.9056	1795951.7313	912.529	94+79.44	-54.64	ALUM. DISK
S2	251815.0386	1796093.3903	911.249	100+21.34	49.14	ALUM. DISK
S3	252421.0238	1796125.1352	900.515	OffChain	OffChain	ALUM. DISK
S4	251841.1988	1795835.9597	914.021	100+28.50	-209.52	ALUM. DISK
S5	251581.3029	1796749.9892	909.700	98+33.74	720.82	ALUM. DISK

TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	3
CONST.	2014	HSIP-10(50)	3



- UTILITY OWNERS LIST**
- TELEPHONE:**
AT&T
116 SOUTH CANON AVENUE
MURFREESBORO, TN 37129
KENNETH KORNEGAY
KK4096@ATT.COM
O: 615-848-2082
C: 615-631-7221
- GAS:**
FAYETTEVILLE GAS
408 COLLEGE STREET WEST
FAYETTEVILLE, TN 37334
RANDALL GRINER
RGRINER@FPU-TN.COM
O: 931-433-1522
- POWER:**
FAYETTEVILLE ELECTRIC
408 COLLEGE STREET WEST
FAYETTEVILLE, TN 37334
EDDIE JACKSON
EJACKSON@FPU-TN.COM
O: 931-433-1522 X146
- WATER & SEWER:**
FAYETTEVILLE PUBLIC UTILITIES
408 COLLEGE STREET WEST
FAYETTEVILLE, TN 37334
DAVID POSEY
DPOSEY@FPU-TN.COM
O: 931-433-1522 X322
- LINCOLN COUNTY BOARD OF PUBLIC UTILITIES**
2863 HUNTSVILLE HWY.
FAYETTEVILLE, TN 37334
BILLY JOE WILEY
LCOBU@FPUNET.COM
O: 931-433-2259
- FIBER OPTICS:**
MEDIA COMM.
DEDRICK STEPHENS
DSTEPHENS@MEDIACOMCC.COM
123 WARE DRIVE
HUNTSVILLE, AL 35811
O: 256-675-0127
- LEVEL 3 COMMUNICATIONS**
TIM BOYKIN
TIM.BOYKIN@LEVEL3.COM
LEVEL3.NETWORKRELOCATIONS@LEVEL3.COM
1025 ELDORADO BLVD., 33A-521
BROOMFIELD, CO. 80021
O: 720-888-7280



UNOFFICIAL SET
NOT FOR BIDDING

COORDINATES ARE NAD/83(1995), ARE DATUM ADJUSTED BY THE FACTOR OF 0.99999 AND TIED TO THE TGN. ALL ELEVATIONS ARE REFERENCED TO THE NAVD 1988.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

PRESENT LAYOUT
S.R. 10 @ S.R. 275
SCALE: 1" = 50'

4/22/2014 8:34:16 AM C:\User\s\RP\MyDesk\top\4-22-14\SR 10 Construction\Construction info\003.sht


TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	3A
CONST.	2014	HSIP-10(50)	3A

95

105

BEGIN PROJ. NO.
52003-3216-94 (CONST)
STA. 99+17.46 (SR 10)
N 251715.0442
E 1796036.7742

END PROJ. NO.
52003-3216-94 (CONST)
STA. 99+77.19 (SR 10)
N 251774.6141
E 1796041.1389



TEAL RD.

NOTES:

- APPROXIMATELY 4' OF THE EXISTING 18" CMP PIPE TO BE REMOVED WHERE DAMAGED AT INLET AND TO ACCOMMODATE PROPOSED JUNCTION BOX. CONTRACTOR TO REPLACE PAVEMENT AROUND PIPE AND JUNCTION BOX.
- WATER VALVES, GAS VALVE, AND FIBER UTILITY LINE IN THE SOUTHEAST CORNER OF THE INTERSECTION MAY NEED TO BE ADJUSTED AND/OR RELOCATED TO ACCOMMODATE PROPOSED SHOULDER AND CULVERT EXTENSION. CONTRACTOR TO COORDINATE WITH UTILITIES.
- EXISTING PAVEMENT MARKINGS IN INTERSECTION BETWEEN PROPOSED STOP LINES TO BE REMOVED.
- PIPES AND DITCHES THAT ARE NOTED ON SURVEY AS FILLED WITH DEBRIS OR BURIED ARE TO BE CLEANED OUT AND RESTORED AS A PART OF THIS PROJECT.
- THE CONTRACTOR SHALL TAKE APPROPRIATE STEPS, BEFORE CLEANING OUT OR REMOVAL/REPLACEMENT OF DITCHES, SIDE DRAINS, AND CROSS DRAINS, TO ENSURE THAT THE DRAINAGE FEATURES/WATERCOURSES ARE NOT STREAMS OR WETLANDS. IF THE CONTRACTOR/TDOT INSPECTOR IS UNSURE WHETHER THE DRAINAGE FEATURES ARE STREAMS OR WETLANDS, THE INSPECTOR SHALL CONTACT THE TDOT ENVIRONMENTAL DIVISION, PERMITS SECTION TO OBTAIN THE APPROPRIATE PERMITS.

MARKING ABBREVIATIONS	
DSYL	- 4" DOUBLE SOLID YELLOW LINE
SSWL	- 4" SINGLE SOLID WHITE LINE
SBYL	- 4" SINGLE BROKEN YELLOW LINE
SBWL	- 4" SINGLE BROKEN WHITE LINE

CATCH BASINS										
SHEET NO.	LOCATION	STATION	OFFSET (FT.)	DRAINAGE CODE	GRATE/TOP ELEV.	STRUCTURE TYPE	OUTSIDE DIMENSIONS (FEET)	DEPTH (FT.)	STANDARD DRAWING	PAY ITEMS JB TYPE 1 611-02.10 0'-4'
3A	S.R. 10	99+53.57	37.73R	2	912.29'	JB	32' X 32'	3.29	D-JBS-1	1
TOTALS										1

STORM DRAINAGE ENDWALLS									
SHEET NO.	LOCATION	STATION	OFFSET (FT.)	DRAINAGE CODE	STRUCTURE TYPE	STANDARD DRAWING	CLASS A CONC. (C.Y.)	REINF. STEEL (LB.)	
3A	S.R.10	99+31.03	38.00' R	1	TYPE "U"	D-PE-18A	0.87	79	
TOTALS								0.87	79


STORM DRAINAGE PIPES										
SHEET NO.	FROM		TO		%	RCP - CLASS III SIZE & LENGTH (L.F.)				BEDDING MATERIAL (C.Y.)
	CODE	OUTLET ELEV.	CODE	INLET ELEV.		18"	24"	30"	36"	
3A	1	909.36'	2	909.12	1.2	20				2.98
TOTALS						20	0	0	0	2.98

UNOFFICIAL SET NOT FOR BIDDING

COORDINATES ARE NAD/83(1995), ARE DATUM ADJUSTED BY THE FACTOR OF 0.999999 AND TIED TO THE TGRN. ALL ELEVATIONS ARE REFERENCED TO THE NAVD 1988.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

PROPOSED LAYOUT
S.R. 10 @ S.R. 275
SCALE: 1" = 50'




TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	3B
CONST.	2014	HSIP-10(50)	3B

STATE OF TENNESSEE DEPARTMENT OF TRANSPORTATION	
PROFILE	
S.R. 10 @ S.R. 275 SCALE: 1"=50' HORIZ. 1"=10' VERT.	

**UNOFFICIAL
SET
NOT FOR
BIDDING**

4/22/2014 8:36:11 AM
C:\User\s\RP\MyDesk\top\4-22-14\SR 10 Construction\Info\003B.SHT



TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	3C
CONST.	2014	HSIP-10(50)	3C

**UNOFFICIAL
SET
NOT FOR
BIDDING**

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

SIDE ROAD
PROFILES

5/8/2014 9:19:45 AM \\FILESERVER\file_server\PROJECTS\2013\13-0602 (SR-10 IS at SR-275 Lincoln County)\Design\Construction\Info\003C.SHT

TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	4
CONST.	2014	HSIP-10(50)	4

D1 TOP-914.11 BOT-913.59 OUT-913.52 4"PVC	D7 INV-905.76 W/STONE ENDWALL
D2 TOP-911.24 BOT-909.40 IN-909.68 4"PVC OUT-909.40	D8 INV-901.93
D3 INV-908.78	D9 INV-901.41
D4 INV-909.12	D10 INV-905.95
D5 INV-908.12	D11 INV-905.25
D6 INV-906.28 W/STONE ENDWALL	D12 INV-903.94
	D13 INV-903.62
	D14 SIZE &TYPE UNKNOWN: PIPE FULL OF DEBRIS

95

BEGIN PROJ. NO.
52003-3216-94 (CONST)
STA. 99+17.46 (SR 10)
N 251715.0442
E 1796036.7742


SR10 STA. 93+50.00
N 251148.9691
E 1795997.2185

W LINCOLN RD STA. 17+50.00
N 251830.7623
E 1795795.0577

105

SR10 STA. 100+00.00 =
W LINCOLN RD STA. 20+00.00=
SR275 STA. 30+00.00
N 251797.3672
E 1796042.8172

SR10 STA. 106+00.00
N 252395.7417
E 1796086.9536



EROSION PREVENTION AND SEDIMENT CONTROL QUANTITIES

ITEM NO.	DESCRIPTION	UNIT	QUANTITY
209-03.22	FILTER SOCK (18 INCH)	L.F.	1650
209-05	SEDIMENT REMOVAL	C.Y.	200
209-08.04	TEMPORARY ENHANCED SILT FENCE	L.F.	60
209-08.07	ROCK CHECK DAM	EACH	9
209-40.33	CATCH BASIN PROTECTION (TYPE D)	EACH	2
303-10.01	MINERAL AGGREGATE (SIZE 57)	TON	5
709-05.06	MACHINED RIP-RAP (CLASS A-1)	TON	23
740-10.03	GEOTEXTILE (TYPE III)	S.Y.	54
801-01	SEEDING (WITH MULCH)	UNIT	1
801-03	WATER (SEEDING & SODDING)	M.G.	0.5
803-01	SOD (NEW SOD)	S.Y.	35

EROSION PREVENTION AND SEDIMENT CONTROL LEGEND

SYMBOL	ITEM	STD. DWG.
** SOCK ** SOCK **	FILTER SOCK	EC-STR-8
◁	ROCK CHECK DAM (V-DITCH)	EC-STR-6
□ D	CATCH BASIN PROTECTION (TYPE D)	EC-STR-19
*ESF*ESF*ESF*	ENHANCED SILT FENCE	EC-STR-3D
⊙	CULVERT PROTECTION (TYPE 1)	EC-STR-11

END PROJ. NO.
52003-3216-94 (CONST)
STA. 99+77.19 (SR 10)
N 251774.6141
E 1796041.1389

- NOTES:
- THE CONTRACTOR SHALL TAKE APPROPRIATE STEPS, BEFORE CLEANING OUT OR REMOVAL/REPLACEMENT OF DITCHES, SIDE DRAINS, AND CROSS DRAINS, TO ENSURE THAT THE DRAINAGE FEATURES/WATERCOURSES ARE NOT STREAMS OR WETLANDS. IF THE CONTRACTOR/TDOT INSPECTOR IS UNSURE WHETHER THE DRAINAGE FEATURES ARE STREAMS OR WETLANDS, THE INSPECTOR SHALL CONTACT THE TDOT ENVIRONMENTAL DIVISION, PERMITS SECTION TO OBTAIN THE APPROPRIATE PERMITS.
 - DUE TO THE TYPE OF WORK IT IS OUR UNDERSTANDING THAT THE PROJECT WILL NOT DISTURB MORE THAN ONE ACRE. IF THE DISTURBED AREA IS MORE THAN ONE ACRE, PLEASE CONTACT THE TDOT ENVIRONMENTAL DIVISION, PERMITS SECTION BECAUSE A NPDES PERMIT WILL BE REQUIRED.

UNOFFICIAL SET
NOT FOR BIDDING

COORDINATES ARE NAD/83(1995), ARE DATUM ADJUSTED BY THE FACTOR OF 0.999999 AND TIED TO THE TGRN. ALL ELEVATIONS ARE REFERENCED TO THE NAVD 1988.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION


EROSION PREVENTION AND SEDIMENT CONTROL PLAN
S.R. 10 @ S.R 275

SCALE: 1"=50'

95

SUMMARY OF QUANTITIES - ITEM NO. 712-06			
SIGN NO.	DESCRIPTION	SIZE (IN.)	NUMBER REQUIRED
G20-2A	END ROAD WORK	48X24	4
W4-2R	LANE ENDS	48X48	1
W5-1	ROAD NARROWS	48X48	1
W8-9A	LOW SHOULDER	36X36	2
W8-11	UNEVEN LANES	36X36	2
W16-2P	500 FT SUPPLEMENTAL PLAQUE	24X18	1
W20-1	ROAD WORK 1/2 MILE	48X48	3
W20-1	ROAD WORK 1500 FEET	48X48	2
W20-1	ROAD WORK 1000 FEET	48X48	2
W20-1	ROAD WORK 500 FEET	48X48	1
W20-1	ROAD WORK AHEAD	48X48	1
W20-5R	RIGHT LANE CLOSED 1000 FEET	48X48	1

TYPE	YEAR	PROJECT NO.	SHEET NO.
CONST.	2014	HS1P-1(050)	6



PAVEMENT EDGE DROP-OFF TRAFFIC CONTROL NOTES:

- A. DIFFERENCES IN ELEVATION BETWEEN ADJACENT TRAFFIC LANES OR TRAFFIC LANE AND SHOULDER WHERE THE TRAFFIC LANE IS BEING USED BY TRAFFIC, CAUSED BY BASE, PAVING OR RESURFACING:
- DIFFERENCES IN ELEVATION BETWEEN ADJACENT ROADWAY ELEMENTS GREATER THAN 0.75 INCH AND NOT EXCEEDING 2 INCHES:
 - WARNING SIGNS, UNEVEN PAVEMENT (W8-11) AND/OR SHOULDER DROP-OFF (W8-9A), SHALL BE PLACED IN ADVANCE OF AND THROUGHOUT THE EXPOSED AREA. MAXIMUM SPACING BETWEEN SIGNS SHALL BE 2,000 FEET WITH A MINIMUM OF 2 SIGNS PER EXPOSED AREA. WHERE UNEVEN PAVEMENT IS ENCOUNTERED, SIGNS SHALL BE PLACED ON EACH SIDE OF THE ROADWAY.
 - DIFFERENCES IN ELEVATION BETWEEN ADJACENT TRAFFIC LANES BEING UTILIZED BY TRAFFIC CAUSED BY ADDED PAVEMENT SHALL BE ELIMINATED WITHIN THREE WORKDAYS.
 - DIFFERENCES IN ELEVATION BETWEEN ADJACENT TRAFFIC LANES BEING UTILIZED BY TRAFFIC CAUSED BY COLD PLANING SHALL BE ELIMINATED WITHIN THREE WORKDAYS.
 - WHEN THE DIFFERENCE IN ELEVATION IS BETWEEN THE TRAFFIC LANE BEING UTILIZED BY TRAFFIC AND SHOULDER, THE DIFFERENCE IN ELEVATION SHALL BE ELIMINATED WITHIN SEVEN WORKDAYS AFTER THE CONDITION IS CREATED.
 - DIFFERENCES IN ELEVATION BETWEEN ADJACENT ROADWAY ELEMENTS GREATER THAN 2 INCHES AND NOT EXCEEDING 6 INCHES, TRAFFIC IS NOT TO BE ALLOWED TO TRAVERSE THIS DIFFERENCE IN ELEVATION:
 - SEPARATION SHALL BE ACCOMPLISHED BY DRUMS, BARRICADES OR OTHER APPROVED DEVICES IN ACCORDANCE WITH THE FOLLOWING:
 - WHERE POSTED SPEEDS ARE 50 MPH OR GREATER, SPACING OF THE PROTECTIVE DEVICES SHALL NOT EXCEED 100 FEET.
 - WHERE POSTED SPEEDS ARE LESS THAN 50 MPH, THE MAXIMUM SPACING OF THE PROTECTIVE DEVICES IN FEET SHALL NOT EXCEED TWICE THE POSTED SPEED IN MILES PER HOUR OR 50 FEET, WHICHEVER SPACING IS GREATER.
 - IF THE DIFFERENCE IN ELEVATION IS ELIMINATED OR DECREASED TO 2 INCHES OR LESS BY THE END OF EACH WORKDAY, CONES MAY BE USED DURING DAYLIGHT HOURS IN LIEU OF DRUMS, BARRICADES OR OTHER APPROVED PROTECTIVE DEVICES MENTIONED IN PARAGRAPH A, PROVIDED WARNING SIGNS ARE ERECTED. WARNING SIGNS (UNEVEN PAVEMENT AND/OR LOW SHOULDER) SHALL BE PLACED IN ADVANCE OF AND THROUGHOUT THE EXPOSED AREA. MAXIMUM SPACING BETWEEN SIGNS SHALL BE 2,000 FEET WITH A MINIMUM OF TWO SIGNS PER EXPOSED AREA. WHERE UNEVEN PAVEMENT IS ENCOUNTERED, SIGNS SHALL BE PLACED ON EACH SIDE OF THE ROADWAY.
 - WHEN THE DIFFERENCE IN ELEVATION IS BETWEEN THE THROUGH TRAFFIC LANE AND THE SHOULDER, AND THE ELEVATION DIFFERENCE IS LESS THAN 3.5 INCHES, THE CONTRACTOR MAY USE WARNING SIGNS AND/OR PROTECTIVE DEVICES AS APPLICABLE AND APPROVED BY THE ENGINEER. SEE PARAGRAPH A REGARDING USE OF DRUMS, BARRICADES OR OTHER APPROVED PROTECTIVE DEVICES. WARNING SIGNS (UNEVEN PAVEMENT AND/OR LOW SHOULDER) WILL BE PLACED IN ADVANCE OF AND THROUGHOUT THE EXPOSED AREA. MAXIMUM SPACING BETWEEN SIGNS SHALL BE 2,000 FEET WITH A MINIMUM OF 2 SIGNS PER EXPOSED AREA. WHERE UNEVEN PAVEMENT IS ENCOUNTERED, SIGNS SHALL BE PLACED ON EACH SIDE OF THE ROADWAY. IN THESE SITUATIONS THE CONTRACTOR SHALL LIMIT HIS OPERATIONS TO ONE WORK ZONE NOT EXCEEDING 2 MILES IN LENGTH UNLESS OTHERWISE NOTED ON THE PLANS OR APPROVED BY THE ENGINEER. ONCE THE CONTRACTOR BEGINS WORK IN A WORK ZONE, A CONTINUOUS OPERATION SHALL BE MAINTAINED UNTIL THE DIFFERENCE IN ELEVATION IS ELIMINATED. SIMULTANEOUS WORK ON SEPARATE ROADWAYS OF DIVIDED HIGHWAYS WILL BE CONSIDERED INDEPENDENTLY IN REGARD TO RESTRICTION OF WORK ZONE ACTIVITY.

TRAFFIC CONTROL LEGEND	
SYMBOL	ITEM
	WORK ZONE
	FLEXIBLE DRUMS (CHANNELIZING) W/ TYPE A WARNING LIGHTS
	SIGN (CONSTRUCTION)

SPECIAL NOTE:
FLEXIBLE DRUM SPACING = 45' FOR TRANSITION SECTIONS
55' FOR TANGENT SECTIONS

- DIFFERENCES IN ELEVATION BETWEEN ADJACENT ROADWAY ELEMENTS GREATER THAN 6 INCHES, BUT NOT EXCEEDING 18 INCHES, THE CONTRACTOR, WITH THE ENGINEER'S APPROVAL, MAY UTILIZE ONE OF THE FOLLOWING:
 - THE CONTRACTOR SHALL ACCOMPLISH SEPARATION BY DRUMS, BARRICADES OR OTHER APPROVED DEVICES IN ACCORDANCE WITH THE FOLLOWING:
 - WHERE POSTED SPEEDS ARE 50 MPH OR GREATER, SPACING OF THE PROTECTIVE DEVICES SHALL NOT EXCEED 100 FEET.
 - WHERE POSTED SPEEDS ARE LESS THAN 50 MPH, THE MAXIMUM SPACING OF THE PROTECTIVE DEVICES IN FEET SHALL NOT EXCEED TWICE THE POSTED SPEED IN MILES PER HOUR OR 50 FEET, WHICHEVER SPACING IS GREATER. IN ORDER TO USE THIS METHOD, THE CONTRACTOR MUST REDUCE THE DIFFERENCE IN ELEVATION TO 6 INCHES OR LESS BY THE END OF THE WORK DAY THAT THE CONDITION IS CREATED.
 - THE CONTRACTOR SHALL PROVIDE DRUMS, BARRICADES OR OTHER APPROVED SEPARATION DEVICES AS SPECIFIED IN PARAGRAPH A, AND CONSTRUCT A STONE WEDGE WITH A 4:1 SLOPE, OR FLATTER, TO ELIMINATE THE VERTICAL OFFSET IF THE LOWER ELEVATION IS AT OR BELOW SUBGRADE AT THE END OF EACH DAY.
 - THE CONTRACTOR SHALL PROVIDE DRUMS, BARRICADES OR OTHER APPROVED SEPARATION DEVICES AS SPECIFIED IN PARAGRAPH A, AND IF THE LOWER ELEVATION IS BASE STONE OR ASPHALT PAVEMENT, PLACEMENT OF SUBSEQUENT LAYERS OF PAVEMENT MUST BEGIN THE NEXT WORK DAY AND PROGRESS CONTINUOUSLY UNTIL THE DIFFERENCE IN ELEVATION IS ELIMINATED OR REDUCED TO 6 INCHES OR LESS.
 - THE CONTRACTOR SHALL PROVIDE SEPARATION BY PORTABLE BARRIER RAIL FOR PRECEDING CONDITIONS A, B, AND C. THE CONTRACTOR SHALL USE THE SHOULDER DROP-OFF WARNING SIGN (W8-9A). IT SHALL BE PLACED IN ADVANCE OF AND THROUGHOUT THE EXPOSED AREA. MAXIMUM SPACING BETWEEN SIGNS SHALL BE 2,000 FEET WITH A MINIMUM OF 2 SIGNS PER EXPOSED AREA. IN THESE SITUATIONS THE CONTRACTOR SHALL LIMIT HIS OPERATIONS TO ONE WORK ZONE NOT EXCEEDING 1 MILE IN LENGTH, UNLESS OTHERWISE NOTED ON THE PLANS OR APPROVED BY THE ENGINEER. ONCE THE CONTRACTOR BEGINS WORK IN A WORK ZONE, A CONTINUOUS OPERATION SHALL BE MAINTAINED UNTIL THE DIFFERENCE IS ELIMINATED. SIMULTANEOUS WORK ON SEPARATE ROADWAYS OF DIVIDED HIGHWAYS WILL BE CONSIDERED INDEPENDENTLY IN REGARD TO RESTRICTION OF WORK ZONE ACTIVITY.
- FOR DIFFERENCES IN ELEVATION BETWEEN ADJACENT ROADWAY ELEMENTS GREATER THAN 18 INCHES, SEPARATION WILL BE PROVIDED BY THE USE OF PORTABLE BARRIER RAIL. IN THIS SITUATION THE CONTRACTOR SHALL LIMIT HIS OPERATIONS TO ONE WORK ZONE NOT EXCEEDING 1 MILE IN LENGTH UNLESS OTHERWISE NOTED ON THE PLANS OR APPROVED BY THE ENGINEER. ONCE THE CONTRACTOR BEGINS WORK IN A WORK ZONE A CONTINUOUS OPERATION SHALL BE MAINTAINED UNTIL THE DIFFERENCE IN ELEVATION IS ELIMINATED. SIMULTANEOUS WORK ON SEPARATE ROADWAYS OF DIVIDED HIGHWAYS WILL BE CONSIDERED INDEPENDENTLY IN REGARD TO RESTRICTION OF WORK ZONE ACTIVITY.







UNOFFICIAL SET
NOT FOR BIDDING

COORDINATES ARE NAD/83(1995), ARE DATUM ADJUSTED BY THE FACTOR OF 0.999999 AND TIED TO THE TGRN. ALL ELEVATIONS ARE REFERENCED TO THE NAVD 1988.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

TRAFFIC CONTROL PLAN
S.R. 10 @ S.R. 275
SCALE: 1" = 50'

TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	6
CONST.	2014	HSIP-10(50)	7



SIGNAL SUPPORT POLE DATA

POLE NO.	STATION	OFFSET	NORTHING	EASTING	GRD ELEV @ POLE	ATTACH ELEV	MOMENT CAPACITY	FOOTING DEPTH
1	100+64.92	49.28' L	251865.74	1795998.45	914.2'	940.2'	504,503 FT-LBS	27'-0" MIN.
2	100+39.59	60.50' R	251832.40	1796106.17	914.1'	940.1'	504,503 FT-LBS	27'-0" MIN.
3	99+24.52	56.41' R	251718.03	1796093.54	917.4'	940.4'	504,503 FT-LBS	27'-0" MIN.
4	99+76.55	54.23' L	251777.97	1795987.01	912.2'	941.2'	504,503 FT-LBS	27'-0" MIN.
5	93+67.23	56.00' L	251170.06	1795942.56	910.4'	939.4'	232,215 FT-LBS	17'-0" MIN.
6	93+67.00	52.25' R	251162.53	1796050.53	915.0'	939.0'	232,215 FT-LBS	17'-0" MIN.


* CONTRACTOR SHALL VERIFY ALL POLE ATTACHMENT HEIGHTS AND OVERHEAD UTILITY CLEARANCES.
** FOOTING DEPTHS BASED ON 4 FOOT DIAMETER FOOTINGS.

MAST ARM SIGNAL SUPPORT POLE DATA

POLE NO.	STATION	OFFSET	NORTHING	EASTING	GRD ELEV @ POLE	ARM ELEVATION	MAST ARM LENGTH	FOOTING DEPTH
7	105+71.80	51.63' L	252371.42	1796033.39	894.1'	922.1'	50'-0"	15'-0" MIN.

* CONTRACTOR SHALL VERIFY ALL POLE ATTACHMENT HEIGHTS AND OVERHEAD UTILITY CLEARANCES.

- NOTES:
- CONTRACTOR IS RESPONSIBLE FOR STAKING POLE LOCATIONS. THESE LOCATIONS MUST BE APPROVED BY THE ENGINEER PRIOR TO WORK COMMENCING.
 - REMOVE EXISTING STOP SIGNS (R1-1) AND STREET NAME SIGNS FROM S.R. 275 AND W. LINCOLN ROAD ONCE SIGNAL IS OPERATIONAL.
 - REMOVE THE EXISTING OVERHEAD FLASHING BEACONS ONCE SIGNAL IS OPERATIONAL.
 - SIGNAL POLES FOR SPAN WIRE ASSEMBLIES MAY BE ADJUSTED UP TO 5' TO AVOID CONFLICTS WITH UTILITIES AS APPROVED BY THE ENGINEER. CONTRACTOR TO VERIFY FOOTING DEPTH, SPAN WIRE LENGTH, AND MINIMUM CABLE BREAKING STRENGTH.
 - SIGNAL POLES FOR MAST ARM MAY BE ADJUSTED UP TO 2' TO AVOID CONFLICTS WITH UTILITIES AS APPROVED BY THE ENGINEER. CONTRACTOR TO VERIFY FOOTING DEPTH AND MAST ARM LENGTH.




UNOFFICIAL SET
NOT FOR BIDDING

COORDINATES ARE NAD/83(1995), ARE DATUM ADJUSTED BY THE FACTOR OF 0.99999 AND TIED TO THE TGRN. ALL ELEVATIONS ARE REFERENCED TO THE NAVD 1988.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

PROPOSED SIGNAL LAYOUT
S.R. 10 @ S.R. 275
SCALE: 1" = 50'



EIGHT PHASE DESIGNATIONS

PHASING NOTES

- (1) MIN RECALL: $\emptyset 2, \emptyset 6$
- (2) PROTECTED/PERMITTED LEFT TURN: $\emptyset 1, \emptyset 5$
- (3) ALL SIGNAL DISPLAYS AND CLEARANCES SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES


BASIC OR SEMI-ACTUATED TIMING (SECS)

PHASE	INITIAL INTERVAL	VEHICLE INTERVAL	MAX I (AM)	MAX I (PM)	CLEARANCE		PEDESTRIAN		RECALL TO	MEMORY POSITION (1)	LEFT TURN OPERATION (2)
					YELLOW	ALL RED	WALK	FLASHING DON'T WALK			
1	7.0	3.0	11.0	11.0	4.0	0.5	-	-	-	NL	P/P
2	20.0	3.0	25.0	28.0	4.0	0.5	-	-	MIN.	-	-
3	-	-	-	-	-	-	-	-	-	-	-
4	10.0	3.0	24.0	16.0	5.0	0.5	-	-	-	NL	PERM
5	7.0	3.0	11.0	11.0	4.0	0.5	-	-	-	NL	P/P
6	20.0	3.0	25.0	28.0	4.0	0.5	-	-	MIN.	-	-
7	-	-	-	-	-	-	-	-	-	-	-
8	10.0	3.0	24.0	16.0	5.0	0.5	-	-	-	NL	PERM

NOTE: TIMINGS ARE INITIAL AND MAY BE ADJUSTED BY THE CONTRACTOR BASED ON FIELD OBSERVATIONS TO PROVIDE EFFICIENT OPERATION.

- (1) NL = NON LOCK
L = LOCK
- (2) PERM = PERMITTED
PROT = PROTECTED
P/P = PROT/PERM

DETECTION LOOP NUMBERING AND FLASHING OPERATION



LOOP AND AMP ASSIGNMENT CHART

ZONE ASSIGNMENT	SIZE	PHASE	MODE	DISTANCE FROM STOP BAR	NUMBER OF TURNS
1-1	6' X 50'	1	PRESENCE	-3'	2-4-2
2-1	6' X 6'	2	PRESENCE	405'	3
2-2	6' X 6'	2	PRESENCE	405'	3
4-1	6' X 50'	4	PRESENCE	-3'	2-4-2
5-1	6' X 50'	5	PRESENCE	-3'	2-4-2
6-1	6' X 6'	6	PRESENCE	405'	3
6-2	6' X 6'	6	PRESENCE	405'	3
8-1	6' X 50'	8	PRESENCE	-3'	2-4-2

LOOP DETECTOR NOTES

- (1) ALL LOOPS ARE 6' IN WIDTH CENTERED IN TRAFFIC LANE. ALL 6' X 50' LOOPS HAVE 2-4-2 TURNS, UNLESS OTHERWISE NOTED.
- (2) LOOP WIRE CONNECTIONS SHALL BE WIRED TO PROVIDE THE APPROPRIATE INDUCTANCE AS REQUIRED BY STD. DWG. T-SG-3.

**UNOFFICIAL SET
NOT FOR BIDDING**

COORDINATE VALUES ARE NAD783 (1995), AND ARE DATUM ADJUSTED BY THE FACTOR OF 1.00009, AND ARE TIED TO THE TENNESSEE GEODETIC REFERENCE NETWORK. ALL ELEVATIONS ARE REFERENCED TO NAVD 1988.


STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

**SIGNAL
DETAILS**

TYPE	YEAR	PROJECT NO.	SHEET NO.
UTIL.	2013	HSIP-10(50)	7
CONST.	2014	HSIP-10(50)	9

TENNESSEE D.O.T.
DESIGN DIVISION

FILE NO.



SR-275
BEGIN STA. 30+50.00
END STA. 31+00.00

**UNOFFICIAL
SET
NOT FOR
BIDDING**

SR-10
BEGIN STA. 99+00.00
END STA. 99+50.00