



- #### GENERAL NOTES
- (A) SIGNS R3-11a, R3-10 AND R3-10a TO BE INSTALLED IN SEQUENCE EVERY HALF MILE
 - (B) ALTERNATE OVERHEAD SIGNS MAY BE USED IF OVERHEAD SIGN STRUCTURE IS AVAILABLE
 - (C) SPECIFIC TIME RESTRICTIONS TO BE DETERMINED BY THE STATE TRAFFIC ENGINEER
 - (D) SEE T-M-5 FOR HOV LANE PAVEMENT MARKINGS
 - (E) SEE T-S-21 FOR SIGN MOUNTING TO BARRIER WALL DETAILS
 - (F) SEE T-S-10 FOR SIGN STIFFENER REQUIREMENTS FOR LARGE SIGNS
 - (G) TO BE USED ON ALL ENTRANCE RAMPS INSIDE THE HOV RESTRICTED AREA.
 - (H) WHERE THE MEDIAN IS INSUFFICIENT, USE TYPICAL HOV SIGN LAYOUT.

MINOR REVISION -- FHWA APPROVAL NOT REQUIRED.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

SIGN LAYOUT
FOR
HOV LANES