


TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION (FOR LANE SHIFTS GREATER THAN 600 m IN LENGTH)



** FOR LANE SHIFTS TO THE LEFT USE W1-4BL FOR 2 LANES, W1-4CL FOR 3 LANES, AND W1-4DL FOR 4 LANES.

* FOR LANE SHIFTS TO THE RIGHT USE W1-4BR FOR 2 LANES, W1-4CR FOR 3 LANES, AND W1-4DR FOR 4 LANES.

X = DISTANCE IN METERS EQUAL TO 0.3 TIMES THE POSTED SPEED

COMPUTATION FOR DISTANCE L

$$L = W \times S$$

L = TAPER LENGTH IN METERS
W = WIDTH OF OFFSET IN METERS
S = POSTED SPEED IN MPH

- GENERAL NOTES**
- (A) PORTABLE BARRIER RAIL WILL BE REQUIRED WHERE DROP OFFS EXCEED 450 mm. PORTABLE BARRIER RAIL MAY BE USED WHERE DROP OFFS EXCEED 150 mm. FOR MORE SPECIFIC INFORMATION SEE TDOT DROP-OFF POLICY.
 - (B) SEE TABLE VI-1 OF PART VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) FOR RECOMMENDED LENGTHS OF BUFFER SPACE.
 - (C) SEE STANDARD DRAWING NO. TM-WZ-10 FOR OTHER NEEDED ADVANCE SIGNING.
 - (D) TAPER LENGTH SHOWN FOR THE PORTABLE BARRIER RAIL IS A MINIMUM. PORTABLE BARRIER RAIL MAY BE EXTENDED BEYOND THE CLEAR ZONE TO ELIMINATE THE NEED FOR AN ATTENUATOR. SEE STANDARD DRAWING RDM-S-11 FOR CLEAR ZONE DISTANCE.

CHANNELIZATION DEVICE LEGEND

	FLEXIBLE DRUMS
	VERTICAL PANELS
	SIGN SUPPORT
	FLEXIBLE DRUMS WITH TYPE "C" WARNING LIGHTS ATTACHED TO BE INSTALLED AT THE EDGE OF PAVEMENT
	DIRECTION OF TRAFFIC
	WORK SITE
	VERTICAL PANEL (SEE STD. DWG. NO. TM-PBR-2 FOR DETAILS AND SPECIFICATIONS)
	ATTENUATOR (SEE STANDARD DRAWINGS)
	RAISED PAVEMENT MARKER (SEE APPROVED QUALIFIED PRODUCT LIST)



ALL UNITS ARE IN MILLIMETERS UNLESS NOTED OTHERWISE.

MINOR REVISION -- FHWA APPROVAL NOT REQUIRED.

STATE OF TENNESSEE
DEPARTMENT OF TRANSPORTATION

LANE SHIFT ON
DIVIDED HIGHWAYS
AND FREEWAYS
(GREATER THAN 600 m)