
☐ REV. 3-15-11: CHANGED SIGN (R2-5A) TO SIGN (W3-5) AND CHANGED FOOTNOTE (). REVISED FLEXIBLE DRUM SPACING AND COMPUTION FOR DISTANCE. REMOVED SIGN R4-1

END

TRAFFIC CONTROL FOR ONE LANE CLOSURE ON MULTI-LANE DIVIDED HIGHWAY (WITH EARLY MERGE)




FOOTNOTES

- (1) APPROVAL OF THE STATE TRAFFIC ENGINEER IS REQUIRED BEFORE PLACING THE "REDUCED SPEED AHEAD" (W3-5) AND THE "SPEED LIMIT" (R2-1) SIGNS.
- (2) ADDITIONAL "ROAD WORK" (W20-1) SIGNS MAY BE USED FOR LONG TRAFFIC QUEUES.

COMPUTATION FOR DISTANCE L

 $L = W X S (FOR S \ge 45 mph)$ $L = Ws^2 / 60 (FOR S \le 40 mph)$

> L = TAPER LENGTH IN FEET W = WIDTH OF OFFSET IN FEET S = POSTED SPEED IN MPH



GENERAL NOTES

- (A) PORTABLE BARRIER RAIL WILL BE REQUIRED WHERE DROP OFFS EXCEED 18 INCHES. PORTABLE BARRIER RAIL MAY BE USED WHERE DROP OFFS EXCEED 6 INCHES. FOR MORE SPECIFIC INFORMATION SEE TDOT DROP-OFF POLICY OR TRAFFIC CONTROL NOTES.
- (B) SEE STANDARD DRAWING NO. T-WZ-10 FOR OTHER NEEDED ADVANCE SIGNING.
- C PORTABLE MESSAGE BOARD SHOULD ONLY BE USED ONLY WHEN TRAFFIC CONDITIONS WARRANT.
- D THIS DETAIL IS TO BE USED FOR WORK ZONES IN BOTH THE LEFT AND RIGHT LANES. WHEN THE WORK ZONE IS IN THE RIGHT LANE, THE "LANE SHIFT" (W1-4AR) SIGN AND THE LANE SHIFT SHALL BE DELETED.
- E REFER TO STANDARD DRAWING NO. T-WZ-11 FOR PORTABLE BARRIER RAIL PLACEMENT, TAPERS, AND END TREATMENT.

■ MINOR REVISION -- FHWA APPROVAL NOT REQUIRED.

STATE OF TENNESSEE DEPARTMENT OF TRANSPORTATION

LANE CLOSURE WITH LEFT HAND MERGE AND LANE SHIFT

T-WZ-21 11-11-04