HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 02S62590013
BRIDGE OWNER: BEDFORD COUNTY

ROAD NAME: **NEW CENTER CHURCH RD**

CROSSING: FLAT CREEK

LATITUDE:: N 35.39125 DEGREES
LONGITUDE: W 86.40966 DEGREES

COUNTY: BEDFORD
ROUTE: 02004
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.35

LON	IGITUDE: W 86.40966 DEGREES	YEAR BUILT: 1958	
MAIN SPAN:	CONCRETE - TEE BEAM	TYPE OF SUPERSTRUCTURE APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ARI ITMENTS:	CONCRETE SPILL THROUGH ARLIT		
BENTS:	TMENTS: CONCRETE SPILL THROUGH ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION TS: CONCRETE PILE BENT ON PILE FOUNDATION		
PIERS:			
FILNO.	CONCRETE HAMMERHEAD PIER OF	NOCK FOUNDATION	
		SCOUR EVALUATION	
	our critical; bridge foundations de sures are installed but they are n	termined to be unstable for calculated scour conditions. No scour eeded.	
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Local Maintenance Personnel	
		[] THP or Local Law Enforcement Personnel	
		[] Other:	
Things to o	hock on a bridge during fleeds		
_	heck on a bridge during floods		
	movement - horizontally as we		
	·	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or ber	nts.	
	k for embankment erosion	h anda	
	k for drift build-up on piers or		
[] - Check pier exposure, if possible, and compare to previous inspection			
[] - Revie	ew the latest bridge inspection	report versus current field conditions	
If Closure is	recommended:		
Coun temp	ty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge		
	The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	n State District maintenance or local highway maintenance ny bridge on the selected detour route shall be checked		
 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 684-7944		
COUNTY SHERIFF'S OFFICE	(931) 836-3232		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 684-4651		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Ins	spection:		
Latest Bridge Inspection Report Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barrica	de Tape printed with the following message:		
SAFETY HAZARD K	EEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24