HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 03017490003

BRIDGE OWNER: CITY OF CAMDEN

ROAD NAME: STIGALL ST

CROSSING: CHARLIE CREEK

LATITUDE:: N 36.06156 DEGREES
LONGITUDE: W 88.09242 DEGREES

COUNTY: BENTON
ROUTE: 01749
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 3.87
YEAR BUILT: 1975

LON	NGHODE. W 86.09242 DEGREES	TEAN BOILT. 1973
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON CONCRETE SPREAD FOOTING FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert
What initiated the Oan out mopeonor.		[] TDOT District or Local Maintenance Personnel
		THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during floods	<u>s:</u>
[] - Span	movement - horizontally as w	ell as vertically
	•	n along curb line, both bridge rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.
[] - Chec	k for embankment erosion	
[] - Chec	k for drift build-up on piers or	bents
[] - Chec	k pier exposure, if possible, ar	nd compare to previous inspection
[] - Revie	w the latest bridge inspection	report versus current field conditions
<u>lf Closure is</u>	recommended:	
Coun temp	ity or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



[] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.			
	lge can be re-opened only after a TDOT bridge inspection team checks the substructure d they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(731) 584-4656		
POLICE OFFICE	(731) 584-4622		
as appropriate, photographs of the bridge ar	spection to BridgeWatch scour monitoring system. If the inspection, a brief summary of findings and, and stream channel measurements. If significant be copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspe	ection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:		
SAFETY HAZARD KE			
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			
Traffic Safety Flares - Minimum of four (4) or set o	f electronic warning flashers		

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)