HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 03SR0690019

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: US641 S

CROSSING: BIRDSONG CREEK

LATITUDE:: N 35.91044 DEGREES LONGITUDE: W 88.10217 DEGREES

COUNTY: BENTON
ROUTE: SR069
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.83

LON	IGITUDE: W 88.10217 DEGREES	}	YEAR BUILT: 1975
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE CONTIL STRINGER/MULTI-BEAM OR GIRDE		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	STEEL PILE FOUNDATION	
BENTS:	CONCRETE COLUMN THREE POST	BENT ON CONCRETE PILE FOUND	DATION
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
	our critical; bridge foundations de ing scour countermeasures.	etermined to be unstable for cal	culated scour conditions. Monitor bridge in
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
	•	[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
[] - Span 1. C 2. C [] - Chec [] - Chec	heck on a bridge during floods movement - horizontally as w Check displacement / deflectio Check for plumb of piers or bei k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar ew the latest bridge inspection	ell as vertically n along curb line, both bridg nts. bents nd compare to previous inspe	
<u>If Closure is</u>	recommended:		
Coun temp	ity or City Maintenance Persor	nnel. Use Barricade Tape, trat rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	maintained)
	(2) City or County Highwa	y Maintenance Official (if br	ridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	vith State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883		
TENNESSEE HIGHWAY PATROL	(731) 423-6635		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the	Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
	cade Tape printed with the following message:		
SAFETY HAZARI	D KEEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24