HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 06022650009

BRIDGE OWNER: BRADLEY COUNTY

ROAD NAME: CHATATA VALLEY RD

CROSSING: CHATATA CREEK

LATITUDE:: N 35.24182 DEGREES
LONGITUDE: W 84.75492 DEGREES

COUNTY: BRADLEY
ROUTE: 02265
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 5.42
YEAR BUILT: 1940

LON	NGITUDE: W 84.75492 DEGREES	YEAR BUILT: 1940
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	TYPE OF SUPERSTRUCTURE R GIRDER APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE SPILL THROUGH ABUT	MENT ON UNKNOWN FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE COLUMNS WITH SOLID UNKNOWN FOUNDATION	WEB WALL (DUMB BELL) ON CONCRETE FOOTING WITH SUB-FOUNDATION
		SCOUR EVALUATION
		ur cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiate	ed the Call-out Inspection?	[] BridgeWatch Alert
	•	[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
[] - Span 1. C 2. C [] - Chec [] - Chec	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, an	ell as vertically n along curb line, both bridge rails and outer edge of bridge deck. hts.
If Closure is	recommended:	
Coun temp	ity or City Maintenance Person	eross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	h State District maintenance or local highway maintenance any bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(423) 728-7141		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 728-7006		
COUNTY SHERIFF'S OFFICE	(423) 728-7301		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the In Latest Bridge Inspection Report	spection:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barrica	ade Tape printed with the following message:		
SAFETY HAZARD	KEEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24