## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 09017140003
BRIDGE OWNER: CARROLL COUNTY
ROAD NAME: LITTLE GROVE RD

CROSSING: BRANCH

LATITUDE:: N 35.91733 DEGREES LONGITUDE: W 88.60014 DEGREES

COUNTY: CARROLL
ROUTE: 01714
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.69
YEAR BUILT: 1970

LON	NGITODE. W 66.00014 DEGREES	TEAN BOILT. 1970
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOU	INDATION
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
	our critical; bridge foundations de sures are installed but they are r	etermined to be unstable for calculated scour conditions. No scour needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
	·	[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
Things to c	heck on a bridge during flood:	<u>s:</u>
[ ] - Span	movement - horizontally as w	ell as vertically
	· · · · · · · · · · · · · · · · · · ·	n along curb line, both bridge rails and outer edge of bridge deck.
2. (	Check for plumb of piers or be	nts.
[ ] - Chec	k for embankment erosion	
[ ] - Chec	k for drift build-up on piers or	bents
[ ] - Chec	k pier exposure, if possible, a	nd compare to previous inspection
[ ] - Revie	ew the latest bridge inspection	report versus current field conditions
<u>If Closure is</u>	<u>s recommended:</u>	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	rill work with State District maintenance or local highway maintenance our route. Any bridge on the selected detour route shall be checked ute.		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
<b>CONTACT PERSONNEL:</b>	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 986-1936		
HWY. CHIEF ADMINISTRATOR'S OF	FICE (731) 986-1998		
COUNTY SHERIFF'S OFFICE	(731) 986-8947		
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to con	nduct the Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above C	hecklist		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole	lone Perriedde Tone printed with the following message:		
	lene Barricade Tape printed with the following message: Y HAZARD KEEP AWAY		
SAFET	I HALAND NEET AVAI		

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape