HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: CARROLL

BRIDGE ID NUMBER: 090A0590001 BRIDGE OWNER: CARROLL COUNTY ROAD NAME: BIG BUCK RD CROSSING: HALLEY CREEK

ROUTE: 0A059 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 36.01697 DEGREES NGITUDE: W 88.57372 DEGREES		LOG MILE: 2.62 YEAR BUILT: 1975	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	PRESTRESSED CONCRETE - BOX B GIRDERS - MULTIPLE	EAM OR APPR. SPA	AN: CONCRETE - CHANNEL BEAM	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOUN	IDATION		
BENTS:	CONCRETE COLUMN TWO POST BE	ON		
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
	our critical; bridge foundations det ling scour countermeasures.	ermined to be unstable for	calculated scour conditions. Monitor bridge in	
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or L	ocal Maintenance Personnel	
		[] THP or Local Law	Enforcement Personnel	
		[] Other:		
[] - Span 1. C 2. C	heck on a bridge during floods movement - horizontally as we Check displacement / deflection Check for plumb of piers or ben k for embankment erosion k for drift build-up on piers or k	II as vertically along curb line, both bri ts.	idge rails and outer edge of bridge deck.	
Check pier exposure, if possible, and compare to previous inspection				
	ew the latest bridge inspection	-	-	
lf Closure is	recommended:			
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape,	secured and properly closed by District, traffic cones and/or traffic flares as ge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is St	ate maintained)	
	(2) City or County Highway	Maintenance Official (i	f bridge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enfo	rcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	vith State District maintenance or local highway maintenance . Any bridge on the selected detour route shall be checked		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 986-1936		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 986-1998		
COUNTY SHERIFF'S OFFICE	(731) 986-8947		
 - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the	Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
	icade Tape printed with the following message:		
SAFETY HAZAR	D KEEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24