## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 09S81480003

BRIDGE OWNER: STATE OF TENNESSEE
ROAD NAME: WHITTHORNE RD
CROSSING: JOHNS CREEK

LATITUDE:: N 35.90428 DEGREES LONGITUDE: W 88.64828 DEGREES

COUNTY: CARROLL
ROUTE: SR220
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 8.36

YEAR BUILT: 1972 TYPE OF SUPERSTRUCTURE APPR. SPAN: NOT APPLICABLE MAIN SPAN-**CONCRETE - CHANNEL BEAM** TYPE OF SUBSTRUCTURE ABUTMENTS: TIMBER CAP ON TIMBER PILE FOUNDATION BENTS: TIMBER PILE BENT ON PILE FOUNDATION PIERS: **NOT APPLICABLE** SCOUR EVALUATION Bridge is scour critical; bridge foundations determined to be unstable for calculated scour conditions. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [ ] BridgeWatch Alert What Initiated the Call-out Inspection? [ 1 TDOT District or Local Maintenance Personnel [ ] THP or Local Law Enforcement Personnel [ ] Other: \_ Things to check on a bridge during floods: [ ] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [ ] - Check for embankment erosion [ ] - Check for drift build-up on piers or bents [ ] - Check pier exposure, if possible, and compare to previous inspection [ ] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [ ] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [ ] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate (4) TDOT Regional Bridge Engineer [ ] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

by a TDOT bridge inspection team.

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	vith State District maintenance or local highway maintenance Any bridge on the selected detour route shall be checked
[ ] - The bridge can be re-opened only after units and they are determined to be str	a TDOT bridge inspection team checks the substructure ructurally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
REGION BRIDGE ENGINEER	(731) 234-9561
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883
TENNESSEE HIGHWAY PATROL	(731) 423-6635
The report shall include the date and tir as appropriate, photographs of the brid	ne inspection to BridgeWatch scour monitoring system. The of the inspection, a brief summary of findings and, The inspection is a brief summary of findings and, The inspection is a significant also be copied to Bridge Inspection Headquarters.
COMMENTS:	
Suggested List of Equipment to conduct the	Inspection:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
	cade Tape printed with the following message:
SAFETY HAZARI	D KEEP AWAY

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24