## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 09SR0010009 COUNTY: CARROLL **BRIDGE OWNER: STATE OF TENNESSEE** ROUTE: SR001 SPECIAL CASE: 0 ROAD NAME: US70 COUNTY SEQUENCE: 1 CROSSING: RUTHERFORD FK OBION RIVE LOG MILE: 11.02 LATITUDE:: **N** 35.90650 DEGREES LONGITUDE: W 88.52086 **DEGREES** YEAR BUILT: 1924 TYPE OF SUPERSTRUCTURE PRESTRESSED CONCRETE CONTINUOUS - BOX APPR. SPAN: NOT APPLICABLE MAIN SPAN-**BEAM OR GIRDERS - SINGLE OR SPREAD** TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE FULL HEIGHT ABUTMENT ON TIMBER PILE FOUNDATION BENTS: **NOT APPLICABLE** PIERS: CONCRETE SOLID SHAFT PIER ON TIMBER PILE FOUNDATION **SCOUR EVALUATION** Bridge is scour critical, but countermeasures have been installed to reduce the risk of bridge failure during a flood event. Deterioration of channel protection or riprap should be reported to TDOT for assessment. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [ ] BridgeWatch Alert What Initiated the Call-out Inspection? [ ] TDOT District or Local Maintenance Personnel [ ] THP or Local Law Enforcement Personnel [ ] Other: Things to check on a bridge during floods: [ ] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [ ] - Check for embankment erosion [ ] - Check for drift build-up on piers or bents [ ] - Check pier exposure, if possible, and compare to previous inspection [ ] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [ ] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [ ] - Contact: (1) District Maintenance Supervisor ( if bridge is State maintained ) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

## **PUBLICATION DATE**

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

[ ] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked
[ ] - The bridge can be re-opened only after a TDOT units and they are determined to be structural	
CONTACT PERSONNEL:	TELEPHONE NUMBER:
REGION BRIDGE ENGINEER	(731) 234-9561
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883
TENNESSEE HIGHWAY PATROL	(731) 423-6635
<ul> <li>Summarize and submit findings from the inspection.</li> <li>The report shall include the date and time of the as appropriate, photographs of the bridge and scouring has occurred, the report shall also be</li> </ul>	e inspection, a brief summary of findings and, stream channel measurements. If significant
COMMENTS:	
Suggested List of Equipment to conduct the Inspect	ion:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	
SAFETY HAZARD KEEP	AWAY
A Barricade Tape Dispenser with serrated cutter	
A roll of Duct Tape	

Traffic Cones - Minimum of four (4)

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone