## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 10S25200001
BRIDGE OWNER: CARTER COUNTY
ROAD NAME: POGA RD

CROSSING: ELK RIVER

LATITUDE:: N 36.25840 DEGREES LONGITUDE: W 81.98358 DEGREES

COUNTY: CARTER
ROUTE: 01429
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.81
YEAR BUILT: 1957

TYPE OF SUPERSTRUCTURE MAIN SPAN: CONCRETE - TEE BEAM APPR. SPAN: NOT APPLICABLE TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE SPILL THROUGH ABUTMENT ON ROCK FOUNDATION BENTS: CONCRETE COLUMN TWO POST BENT ON ROCK FOUNDATION PIERS: CONCRETE SOLID SHAFT PIER ON ROCK FOUNDATION SCOUR EVALUATION Bridge is scour critcal; Bridge has failed and is closed to traffic. Substructure units are founded on rock. **INSPECTION PROCEDURES** What Initiated the Call-out Inspection? [ ] BridgeWatch Alert [ ] TDOT District or Local Maintenance Personnel [ ] THP or Local Law Enforcement Personnel [ ] Other: Things to check on a bridge during floods: [ ] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [ ] - Check for embankment erosion [ ] - Check for drift build-up on piers or bents [ ] - Check pier exposure, if possible, and compare to previous inspection [ ] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [ ] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [ ] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained)

## **PUBLICATION DATE**

(2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

[ ] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ork with State District maintenance or local highway maintenance oute. Any bridge on the selected detour route shall be checked
[ ] - The bridge can be re-opened only units and they are determined to l	after a TDOT bridge inspection team checks the substructure be structurally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(423) 542-1801
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 543-2331
COUNTY SHERIFF'S OFFICE	(423) 543-2211
The report shall include the date a as appropriate, photographs of the	om the inspection to BridgeWatch scour monitoring system. and time of the inspection, a brief summary of findings and, e bridge and stream channel measurements. If significant shall also be copied to Bridge Inspection Headquarters.
COMMENTS:	
Suggested List of Equipment to conduc	t the Inspection:
Latest Bridge Inspection Report	1.11-4
Scour POA Report with the above Check	Klist
Bridge Design Plans, if available  Tape measure with weight	
Plumb bob	
Range Pole	
_	Barricade Tape printed with the following message:
	ZARD KEED AWAY

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24