HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 110A0120001
BRIDGE OWNER: CHEATHAM COUNTY
ROAD NAME: HOUSTON FIELDER RD
CROSSING: HALF PONE CREEK

LATITUDE:: N 36.37332 DEGREES LONGITUDE: W 87.21685 DEGREES

COUNTY: CHEATHAM
ROUTE: 0A012
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.79
YEAR BUILT: 1981

		TYPE OF SUPI	RSTRUCTURE =		
MAIN SPAN:	PRESTRESSED CONCRETE CONTIN	IUOUS -	APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUI	STRUCTURE -		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION				
BENTS:	S: NOT APPLICABLE				
PIERS: CONCRETE HAMMERHEAD PIER ON CONCRETE SPREAD FOOTING FOUNDATION				DUNDATION	
		SCOUR EV	ALUATION =		
	inknown foundations. Risk of sco icant flood events. Monitor bridge			bridge shall be monitored for distress termeasures.	
		INSPECTION	PROCEDURES -		
What Initiated the Call-out Inspection?		[] Bridge	Watch Alert		
		[] TDOT	District or Loca	Il Maintenance Personnel	
		[] THP o	r Local Law Enf	orcement Personnel	
		[] Other:	:		
[] - Span 1. C 2. C [] - Chec [] - Chec [] - Revie	Check for plumb of piers or ber k for embankment erosion k for drift build-up on piers or l k pier exposure, if possible, an ew the latest bridge inspection	ell as vertical n along curb nts. bents d compare to	line, both bridge		
<u>If Closure is </u>	recommended:				
Coun temp	ity or City Maintenance Person	nel. Use Barr	icade Tape, traf	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	maintained)				
	(2) City or County Highway	y Maintenanc	e Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or lo	cal law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer			
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	e District maintenance or local highway maintenance dge on the selected detour route shall be checked				
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.				
CONTACT PERSONNEL:	TELEPHONE NUMBER:				
COUNTY MAYOR'S OFFICE	(615) 792-4316				
HWY. CHIEF ADMINISTRATOR'S OFFICE	(615) 792-4240				
COUNTY SHERIFF'S OFFICE	(615) 792-4341				
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.					
COMMENTS:					
Suggested List of Equipment to conduct the Inspection Latest Bridge Inspection Report Scour POA Report with the above Checklist	on:				
Bridge Design Plans, if available					
Tape measure with weight					
Plumb bob					
Range Pole					
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:				
CAEETY HAZARD KEED					

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)