HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 110A2270001

BRIDGE OWNER: TOWN OF ASHLAND CITY

ROAD NAME: FORREST ST CROSSING: DRY CREEK

LATITUDE:: N 36.26275 DEGREES LONGITUDE: W 87.04253 DEGREES

COUNTY: CHEATHAM
ROUTE: 0A227
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.49

YEAR BUILT: 1970 TYPE OF SUPERSTRUCTURE MAIN SPAN: PRESTRESSED CONCRETE CONTINUOUS -APPR SPAN: NOT APPLICABLE STRINGER/MULTI-BEAM OR GIRDER TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION BENTS: **NOT APPLICABLE** PIERS: CONCRETE HAMMERHEAD PIER ON CONCRETE SPREAD FOOTING FOUNDATION **SCOUR EVALUATION** Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** What Initiated the Call-out Inspection? [] BridgeWatch Alert [] TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained)

PUBLICATION DATE

(3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TD units and they are determined to be structure.	OT bridge inspection team checks the substructure ally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
CITY MAYOR'S OFFICE	(615) 792-4211
POLICE OFFICE	(615) 792-5618
PUBLIC WORKS DIRECTOR	(615) 792-7553
as appropriate, photographs of the bridge an	pection to BridgeWatch scour monitoring system. the inspection, a brief summary of findings and, id stream channel measurements. If significant be copied to Bridge Inspection Headquarters.
COMMENTS:	
Suggested List of Equipment to conduct the Inspe	ction:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:
SAFETY HAZARD KEE	P AWAY

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19