HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 11S63310009

BRIDGE OWNER: CHEATHAM COUNTY
ROAD NAME: OLD CLARKSVILLE PIKE
CROSSING: SYCAMORE CREEK

LATITUDE:: N 36.34565 DEGREES LONGITUDE: W 87.02898 DEGREES

COUNTY: CHEATHAM
ROUTE: 00958
SPECIAL CASE: 0
COUNTY SEQUENCE: 2
LOG MILE: 9.63
YEAR BUILT: 1960

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	CONCRETE CONTINUOUS - TEE BEA		CONCRETE - TEE BEAM	
		TYPE OF SUBSTRUCTURE =		
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S			
BENTS:				
PIERS:	CONCRETE SOLID SHAFT PIER ON	ROCK FOUNDATION		
		SCOUR EVALUATION =		
Bridge is see	our critical: bridge foundations de		culated scour conditions. Rip-rap protection	
	stalled but is in poor condition. Sign			
		INSPECTION PROCEDURES =		
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert		
		[] TDOT District or Loca	al Maintenance Personnel	
		[] THP or Local Law Enf	orcement Personnel	
		[] Other:		
Things to c	<u>heck on a bridge during floods</u>	<u>:</u>		
[] - Span	movement - horizontally as we	ell as vertically		
1. (Check displacement / deflection	along curb line, both bridge	e rails and outer edge of bridge deck.	
	Check for plumb of piers or ben	its.		
	k for embankment erosion			
	k for drift build-up on piers or l			
[] - Check pier exposure, if possible, and compare to previous inspection				
[] - Revie	ew the latest bridge inspection	report versus current field c	onditions	
If Closure is	recommended:			
[] - Stav	at bridge with vehicle pulled ac	ross road until bridge is sec	cured and properly closed by District.	
	at bridge with vehicle pulled across road until bridge is secured and properly closed by District, inty or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as			
		ists to stay off of the bridge	until such time as the bridge may	
-	operly closed and barricaded.	on and an Athernal of Otata		
[] - Cont	act: (1) District Maintenance S		-	
		·	idge is not State maintained)	
	(3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate (4) TDOT Regional Bridge Engineer			
[] The P	` ,	•	daylight visual inspection is made	
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bri prior to signing the detour route. 	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(615) 792-4316		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(615) 792-4240		
COUNTY SHERIFF'S OFFICE	(615) 792-4341		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspecti Latest Bridge Inspection Report	on:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole A 1000 Foot Roll of yellow Polyethylene Barricade Ta	no printed with the following message:		
CAFETY HAZARD KEED			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24