HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 14SR0530001

BRIDGE OWNER: STATE OF TENNESSEE
ROAD NAME: GAINESBORO HWY
CROSSING: DRY FORK CREEK

LATITUDE:: N 36.48315 DEGREES LONGITUDE: W 85.56218 DEGREES

COUNTY: CLAY
ROUTE: SR053
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.35
YEAR BUILT: 1961

	_	TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	CONCRETE CONTINUOUS - TEE BEA		CONCRETE - TEE BEAM	
	_	TYPE OF SUBSTRUCTURE -		
ABI ITMENTS:	CONCRETE STUB ABUTMENT ON ST			
BENTS:	CONCRETE COLUMN TWO POST BE			
PIERS:	NOT APPLICABLE	NT ON ROOK TOOKDATION		
TILINO.	NOT ALL LIOABLE			
		SCOUR EVALUATION -		
•	our critical; bridge foundations dete ling scour countermeasures.	ermined to be unstable for cal	culated scour conditions. Monitor bridge in	
		INSPECTION PROCEDURES -		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Loca	Il Maintenance Personnel	
		[] THP or Local Law Enf	orcement Personnel	
		[] Other:		
Things to c	heck on a bridge during floods:			
1. (movement - horizontally as we Check displacement / deflection Check for plumb of piers or bent	along curb line, both bridge	e rails and outer edge of bridge deck.	
	k for embankment erosion			
[] - Check for drift build-up on piers or bents				
[] - Check pier exposure, if possible, and compare to previous inspection				
[] - Review the latest bridge inspection report versus current field conditions				
	, a uno unico annugo mopocino.			
If Closure is	recommended:			
 Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. 				
[] - Conta	maintained)			
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)	
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•	ment Officers as appropriate	
	(4) TDOT Regional Bridge B	Engineer		
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(423) 290-7467		
DISTRICT MAINTENANCE SUPERVISOR	(931) 267-6324		
TENNESSEE HIGHWAY PATROL	(931) 528-8496		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	ion:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			
SAFETY HAZARD KEEP	AWAY		

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)