## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 160A0300005
BRIDGE OWNER: COFFEE COUNTY
ROAD NAME: OLD MANCHESTER HWY
CROSSING: HICKERSON SPRINGS BRANCH
LATITUDE:: N 35.41078 DEGREES

LONGITUDE: W 86.13045 DEGREES

ROUTE: 0A030
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 3.18
YEAR BUILT: 1934

COUNTY: COFFEE

		TYPE OF SUPERSTRUCTURE =	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE SOLID SHAFT PIER ON	UNKNOWN FOUNDATION	
		SCOUR EVALUATION -	
Bridge has u	ınknown foundations. Risk of sco	our cannot be determined. The	bridge shall be monitored for distress
during signif	icant flood events. Monitor bridge	e in lieu of installing scour coun	termeasures.
		INSPECTION PROCEDURES -	
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
		[ ] TDOT District or Loca	al Maintenance Personnel
		[ ] THP or Local Law Enf	forcement Personnel
		[ ] Other:	
Things to c	<u>heck on a bridge during floods</u>	<u>::</u>	
[ ] - Span	movement - horizontally as we	ell as vertically	
1. 0	Check displacement / deflection	n along curb line, both bridge	e rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or ber	nts.	
[ ] - Chec	k for embankment erosion		
[ ] - Chec	k for drift build-up on piers or	bents	
[ ] - Chec	k pier exposure, if possible, ar	d compare to previous inspe	ection
[ ] - Revie	ew the latest bridge inspection	report versus current field c	onditions
lf Closure is	recommended:		
Coun temp	ity or City Maintenance Person	nel. Use Barricade Tape, traf	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	idge is not State maintained )
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 723-5100		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 728-3321		
COUNTY SHERIFF'S OFFICE	(931) 728-3591		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.</li> <li>The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect Latest Bridge Inspection Report Security BOA Benefit with the characterists	tion:		
Scour POA Report with the above Checklist Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:		
CAFETY HAZARD KEED			

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24