## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 160A2310001

BRIDGE OWNER: COFFEE COUNTY

ROAD NAME: HANKERSMITH RD

CROSSING: CRUMPTON CREEK

LATITUDE:: N 35.39175 DEGREES

ROUTE: 0A231
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.27
YEAR BUILT: 1940

COUNTY: COFFEE

| LON   | NGITUDE: W 86.11217 DEGREES  | YEAR BUILT: 1940   |  |
|---|--|--|--|
| MAIN SPAN:  | CONCRETE CONTINUOUS - CULVEI<br>FRAME CULVERTS)  | TYPE OF SUPERSTRUCTURE  RT (INCLUDES APPR. SPAN: NOT APPLICABLE  |  |
|   |  | TYPE OF SUBSTRUCTURE   |  |
| ABUTMENTS:<br>BENTS:  | CONCRETE BOX TYPE ON CONCRE  | TE SPREAD FOOTING FOUNDATION   |  |
| PIERS:  | PIER WALL FOR CONCRETE BOX C   | N CONCRETE SPREAD FOOTING FOUNDATION   |  |
|   |  | SCOUR EVALUATION   |  |
|   |  | ur cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.   |  |
|   |  | INSPECTION PROCEDURES  |  |
| What Initiated the Call-out Inspection?                               |  | [ ] BridgeWatch Alert  |  |
|   |  | [ ] TDOT District or Local Maintenance Personnel   |  |
|   |  | [ ] THP or Local Law Enforcement Personnel   |  |
|   |  | [ ] Other:   |  |
| [ ] - Span<br>1. C<br>2. C<br>[ ] - Chec<br>[ ] - Chec<br>[ ] - Revie | Check for plumb of piers or ber<br>k for embankment erosion<br>k for drift build-up on piers or<br>k pier exposure, if possible, an<br>ew the latest bridge inspection | ell as vertically<br>n along curb line, both bridge rails and outer edge of bridge deck.<br>hts.   |  |
| <u>if Ciosure is</u>  | recommended:   |  |  |
| Coun<br>temp  | ity or City Maintenance Person   | cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may |  |
| [ ] - Conta   | ` '  | upervisor ( if bridge is State maintained )  |  |
|   |  | y Maintenance Official (if bridge is not State maintained)   |  |
|   |  | etrol and/or local law enforcement Officers as appropriate   |  |
|   | (4) TDOT Regional Bridge   | •  |  |
|   | ] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.                                 |  |  |

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



| <ul> <li>The bridge inspection team will work with State<br/>officials in establishing a detour route. Any brid<br/>prior to signing the detour route.</li> </ul>   | District maintenance or local highway maintenance ge on the selected detour route shall be checked  |  |  |
|---|---|--|--|
|   | <ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure<br/>units and they are determined to be structurally stable.</li> </ul> |  |  |
| CONTACT PERSONNEL:  | TELEPHONE NUMBER:   |  |  |
| COUNTY MAYOR'S OFFICE   | (931) 723-5100  |  |  |
| HWY. CHIEF ADMINISTRATOR'S OFFICE   | (931) 728-3321  |  |  |
| COUNTY SHERIFF'S OFFICE   | (931) 728-3591  |  |  |
| <ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul> |   |  |  |
| COMMENTS:   |   |  |  |
| Suggested List of Equipment to conduct the Inspection   | <u>n:</u>   |  |  |
| Latest Bridge Inspection Report   |   |  |  |
| Scour POA Report with the above Checklist   |   |  |  |
| Bridge Design Plans, if available   |   |  |  |
| Tape measure with weight  |   |  |  |
| Plumb bob   |   |  |  |
| Range Pole  | o printed with the following massage:   |  |  |
| A 1000 Foot Roll of yellow Polyethylene Barricade Tap<br>SAFETY HAZARD KEEP A   |   |  |  |
| SAFELL HAZARU KEEP A  | AVVA I  |  |  |

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)