## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: CROCKETT

BRIDGE ID NUMBER: 17015680003

BRIDGE OWNER: CROCKETT COUNTY

ROAD NAME: LOWER JACKSON RD

CROSSING: BR SO FK OF FK DEER R

LATITUDE:: N 35.69839 DEGREES

ROUTE: 01568
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.18

LONGITUDE: W 89.04469 **DEGREES** YEAR BUILT: 1962 TYPE OF SUPERSTRUCTURE = APPR. SPAN: NOT APPLICABLE MAIN SPAN-STEEL - STRINGER/MULTI-BEAM OR GIRDER TYPE OF SUBSTRUCTURE ABUTMENTS: TIMBER CAP ON TIMBER PILE FOUNDATION BENTS: **NOT APPLICABLE** PIERS: **NOT APPLICABLE** SCOUR EVALUATION Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [ ] BridgeWatch Alert What Initiated the Call-out Inspection? [ 1 TDOT District or Local Maintenance Personnel [ ] THP or Local Law Enforcement Personnel [ ] Other: Things to check on a bridge during floods: [ ] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [ ] - Check for embankment erosion [ ] - Check for drift build-up on piers or bents [ ] - Check pier exposure, if possible, and compare to previous inspection [ ] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [ ] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [ ] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate (4) TDOT Regional Bridge Engineer [ ] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

by a TDOT bridge inspection team.

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	<ul> <li>The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.</li> </ul>		
	bridge can be re-opened only after a TDOT bridge inspection team checks the substructure as and they are determined to be structurally stable.		
	CONTACT PERSONNEL:	TELEPHONE NUMBER:	
	COUNTY MAYOR'S OFFICE	(731) 696-5460	
	HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 696-2244	
	COUNTY SHERIFF'S OFFICE	(731) 696-2104	
 -	] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMME	ENTS:		
Sugge	ested List of Equipment to conduct the Inspec	ction:	
	Bridge Inspection Report		
	POA Report with the above Checklist		
_	e Design Plans, if available		
•	neasure with weight · ·		
Plumb			
Range		The state of the day of the fall and the state of the sta	
A 1000	Foot Roll of yellow Polyethylene Barricade		
	SAFETY HAZARD KEE	PAWAY	

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape