## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 170A1910001 BRIDGE OWNER: CROCKETT COUNTY

ROAD NAME: WARREN RD

CROSSING: BRANCH OF CYPRESS CREEK

COUNTY: CROCKETT ROUTE: 0A191 SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.76139 DEGREES IGITUDE: W 89.07567 DEGREES			
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	WOOD OR TIMBER - STRINGER/MU GIRDER	JLTI-BEAM OR APPR. SPAN: NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE		
	TIMBER CAP ON TIMBER PILE FOL			
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION		
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
		our cannot be determined. The bridge shall be monitored for distress		
during signiii	icani nood evenis. Monitor bridg	e in lieu of installing scour countermeasures.		
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert		
		[ ] TDOT District or Local Maintenance Personnel		
		[ ] THP or Local Law Enforcement Personnel		
		[ ] Other:		
Things to al	haalaan a buidaa duuina flaad			
_	heck on a bridge during flood			
	movement - horizontally as w	•		
	<u>-</u>	n along curb line, both bridge rails and outer edge of bridge deck.		
	Check for plumb of piers or be	nts.		
	k for embankment erosion	honte		
	<ul><li>[ ] - Check for drift build-up on piers or bents</li><li>[ ] - Check pier exposure, if possible, and compare to previous inspection</li></ul>			
		report versus current field conditions		
[ ] Novic	The latest bridge mopeotion	Troport versus surrent field sofiditions		
<u>lf Closure is</u>	recommended:			
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may		
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )		
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )		
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate		
	(4) TDOT Regional Bridge	Engineer		
	idge should remain closed until the water recedes and a daylight visual inspection is made DOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any bri prior to signing the detour route.</li> </ul>	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 696-5460		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 696-2244		
COUNTY SHERIFF'S OFFICE	(731) 696-2104		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspecti	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available  Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP			

**TDOT radio directory (State Personnel only)** 

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape