## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 18SR0680005

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR68

CROSSING: GRASSY COVE CREEK

LATITUDE:: N 35.83767 DEGREES

LONGITUDE: W 84.91733 DEGREES

COUNTY: CUMBERLAND
ROUTE: SR068
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.13

LON	IGITUDE: W 84.91733 DEGREES	YEAR BUILT: 1951
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON C	ONCRETE PILE FOUNDATION
BENTS:	CONCRETE PILE BENT ON CONCRE	TE PILE FOUNDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
	our critical; bridge foundations de stalled and is in good condition.	termined to be unstable for calculated scour conditions. Rip-rap protection
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
	•	[ ] TDOT District or Local Maintenance Personnel
		[ ] THP or Local Law Enforcement Personnel
		[ ] Other:
[ ] - Span	heck on a bridge during floods movement - horizontally as we Check displacement / deflection	
2. 0	Check for plumb of piers or ber	ts.
[ ] - Chec	k for embankment erosion	
[ ] - Chec	k for drift build-up on piers or l	pents
[ ] - Chec	k pier exposure, if possible, an	d compare to previous inspection
[ ] - Revie	ew the latest bridge inspection	report versus current field conditions
If Closure is	recommended:	
		areas road until bridge is secured and properly closed by District
Coun temp	ity or City Maintenance Person	ross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as stay off of the bridge until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State maintained )
	(2) City or County Highway	/ Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	e District maintenance or local highway maintenance dge on the selected detour route shall be checked		
	- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(423) 290-7467		
DISTRICT MAINTENANCE SUPERVISOR	(931) 267-6324		
TENNESSEE HIGHWAY PATROL	(931) 528-8496		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and,             as appropriate, photographs of the bridge and stream channel measurements. If significant             scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	ion:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			
SAFETY HAZARD KEEP	AWAY		

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)