HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 18SR0680007 COUNTY: CUMBERLAND

BRIDGE OWNER: STATE OF TENNESSEE

ROAD NAME: SR68

CROSSING: GRASSY COVE CREEK
LATITUDE:: N 35.83509 DEGREES
LONGITUDE: W 84.91560 DEGREES

ROUTE: SR068
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.54
YEAR BUILT: 1951

20.	10.100E. 11 04.01000 DEGREE	12/11/20121. 1001
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION
BENTS: CONCRETE PILE BENT ON CONCRETE PILE FOUNDATION		ETE PILE FOUNDATION
PIERS:	NOT APPLICABLE	
		COOLID EVALUATION
Delates in a		SCOUR EVALUATION
		etermined to be unstable for calculated scour conditions. Rip-rap protection me minor repairs to the protection system are needed.
		- INSPECTION PROCEDURES -
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	to dath a Call and Incorportion 2	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	heck on a bridge during flood	<u>S:</u>
[] - Span	n movement - horizontally as w	ell as vertically
1. (Check displacement / deflection	n along curb line, both bridge rails and outer edge of bridge deck.
2. (Check for plumb of piers or be	nts.
[] - Chec	k for embankment erosion	
[] - Chec	k for drift build-up on piers or	bents
[] - Chec	k pier exposure, if possible, a	nd compare to previous inspection
[] - Revie	ew the latest bridge inspection	report versus current field conditions
		•
<u>If Closure is</u>	recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer Engineer
[] - The E	Bridge should remain closed ບ	ntil the water recedes and a daylight visual inspection is made
by a	TDOT bridge inspection team.	•

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



		te District maintenance or local highway maintenance idge on the selected detour route shall be checked	
[]-	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
	CONTACT PERSONNEL:	TELEPHONE NUMBER:	
	REGION BRIDGE ENGINEER	(423) 290-7467	
	DISTRICT MAINTENANCE SUPERVISOR	(931) 267-6324	
	TENNESSEE HIGHWAY PATROL	(931) 528-8496	
COMMI	ENTS:		
	ested List of Equipment to conduct the Inspect	ion:	
	Bridge Inspection Report POA Report with the above Checklist		
	e Design Plans, if available		
_	measure with weight		
Plumb	bob		
Range	e Pole		
A 1000	Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:	
	SAFETY HAZARD KEED	ΔWΔΥ	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24