HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 190E0800001 COUNTY: DAVIDSON

BRIDGE OWNER: NASHVILLE DEPARTMENT OF TRANSPORTATION

ROAD NAME: **GEORGIA AVE**CROSSING: **RICHLAND CREEK**

LATITUDE:: N 36.15460 DEGREES
LONGITUDE: W 86.85405 DEGREES

ROUTE: 0D152
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.46
YEAR BUILT: 1940

		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	CONCRETE CONTINUOUS - TEE BEA		NOT APPLICABLE	
		TYPE OF CURCTURE -		
A DI ITMENITO.	CONCRETE FULL UFICUT ABUTMEN	TYPE OF SUBSTRUCTURE =	ON	
	CONCRETE FULL HEIGHT ABUTMEN		ON	
BENTS: PIERS:	CONCRETE COLUMN TWO POST BE	NT ON PILE FOUNDATION		
PIERS.	NOT APPLICABLE			
		SCOUR EVALUATION -		
	inknown foundations. Risk of sco icant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.	
		INSPECTION PROCEDURES =		
What Initiated the Call-out Inspection? [] BridgeWatch Alert				
		[] TDOT District or Loca	al Maintenance Personnel	
		[] THP or Local Law Enf	forcement Personnel	
		[] Other:		
Things to cl	heck on a bridge during floods	<u>.</u>		
1. C	movement - horizontally as we check displacement / deflection check for plumb of piers or ben	along curb line, both bridge	e rails and outer edge of bridge deck.	
[] - Check for embankment erosion				
[] - Check for drift build-up on piers or bents				
[] - Check pier exposure, if possible, and compare to previous inspection				
[] - Review the latest bridge inspection report versus current field conditions				
f Closure is	recommended:			
] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.				
[] - Conta	act: (1) District Maintenance Su	pervisor (if bridge is State	maintained)	
	(2) City or County Highway	Maintenance Official (if br	idge is not State maintained)	
	(3) Tennessee Highway Pa	trol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge		-	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



officials in establishing a detour route. Any bridge prior to signing the detour route.	District maintenance or local highway maintenance ge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TDOT be units and they are determined to be structurally	
CONTACT PERSONNEL:	TELEPHONE NUMBER:
CITY ENGINEER'S OFFICE	(615) 862-8760
POLICE OFFICE	(615) 762-7400
[] - Summarize and submit findings from the inspect The report shall include the date and time of the inspect as appropriate, photographs of the bridge and st scouring has occurred, the report shall also be con-	inspection, a brief summary of findings and, ream channel measurements. If significant
COMMENTS:	
Suggested List of Equipment to conduct the Inspection	<u>n:</u>
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	e printed with the following message:
SAFETY HAZARD KEEP A	WAY
A Barricade Tape Dispenser with serrated cutter	
A roll of Duct Tape	
Traffic Cones - Minimum of four (4)	

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)