HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 20017390001
BRIDGE OWNER: DECATUR COUNTY
ROAD NAME: BUINCH CHAPEL RD
CROSSING: TERRAPIN CREEK

LATITUDE:: N 35.67200 DEGREES LONGITUDE: W 88.07878 DEGREES

COUNTY: DECATUR
ROUTE: 01739
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.25
VEAR BUILT: 1076

LON	NGITUDE: W 88.07878 DEGREES		YEAR BUILT: 1976
MAIN SPAN:	CONCRETE - BOX BEAM OR GIRDE	TYPE OF SUPERSTRUCTURE RS - MULTIPLE APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
Bridge has u	inknown foundations. Risk of sco		bridge shall be monitored for distress
•	icant flood events. Monitor bridge		•
		INSPECTION PROCEDURES	
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert	
			al Maintenance Personnel
			forcement Personnel
		[] Other:	
Things to c	heck on a bridge during floods	<u>s:</u>	
[] - Span	movement - horizontally as w	ell as vertically	
			e rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.	
[] - Chec	k for embankment erosion		
[] - Chec	k for drift build-up on piers or	bents	
[] - Chec	k pier exposure, if possible, ar	nd compare to previous insp	ection
[] - Revie	ew the latest bridge inspection	report versus current field o	conditions
<u>lf Closure is</u>	recommended:		
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	e maintained)
	(2) City or County Highwa	y Maintenance Official (if b	ridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State I officials in establishing a detour route. Any bridg prior to signing the detour route. 				
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(731) 852-2131			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 852-2511			
COUNTY SHERIFF'S OFFICE	(731) 852-2183			
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 				
COMMENTS:				
Suggested List of Equipment to conduct the Inspection	<u>u</u>			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barricade Tape				
SAFETY HAZARD KEEP AV	NAY			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24