## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 20017580005
BRIDGE OWNER: DECATUR COUNTY
ROAD NAME: WHITES CREEK RD
CROSSING: WHITES CREEK

LATITUDE:: N 35.50747 DEGREES LONGITUDE: W 87.98944 DEGREES

COUNTY: DECATUR
ROUTE: 01758
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 7.80
YEAR BUILT: 1945

LON	NGHODE. W 67.96944 DEGREES		TEAN BOILT. 1943
		TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON U	INKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE COLUMNS WITH SOLID	WEB WALL (DUMB BELL) ON UNK	NOWN FOUNDATION
		SCOUR EVALUATION =	
Bridge has u	inknown foundations. Risk of soc		bridge shall be monitored for distress
	icant flood events. Monitor bridge		
		INSPECTION PROCEDURES =	
What Initiate	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
What initiated the dan dat inspection		•	Il Maintenance Personnel
		[ ] THP or Local Law Enf	
Things to cl	heck on a bridge during floods	<u>s:</u>	
[ ] - Span	movement - horizontally as w	ell as vertically	
	•		e rails and outer edge of bridge deck.
	Check for plumb of piers or bei		
	k for embankment erosion		
[ ] - Chec	k for drift build-up on piers or	bents	
[ ] - Chec	k pier exposure, if possible, ar	nd compare to previous inspe	ection
[ ] - Revie	w the latest bridge inspection	report versus current field co	onditions
<u>lf Closure is</u>	recommended:		
Coun temp	ity or City Maintenance Person	nel. Use Barricade Tape, traf	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	upervisor ( if bridge is State	maintained )
	(2) City or County Highwa	y Maintenance Official ( if br	idge is not State maintained )
	(3) Tennessee Highway Pa	atrol and/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
	Bridge should remain closed un TDOT bridge inspection team.	ntil the water recedes and a c	laylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route prior to signing the detour route.	e. Any bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(731) 852-2131	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 852-2511	
COUNTY SHERIFF'S OFFICE	(731) 852-2183	
as appropriate, photographs of the brid	ime of the inspection, a brief summary of findings and, dge and stream channel measurements. If significant I also be copied to Bridge Inspection Headquarters.	
Suggested List of Equipment to conduct the	Inspection:	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
	cicade Tape printed with the following message:	
SAFETY HAZAR	D KEEP AWAY	

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24