HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 22003430003

BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: YELLOW CREEK RD

CROSSING: BRANCH

LATITUDE:: N 36.12435 DEGREES LONGITUDE: W 87.49318 DEGREES

COUNTY: DICKSON
ROUTE: SR046
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 15.59

YEAR BUILT: 1940 TYPE OF SUPERSTRUCTURE MAIN SPAN: **CONCRETE - TEE BEAM** APPR. SPAN: NOT APPLICABLE TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION BENTS: **NOT APPLICABLE** PIERS: CONCRETE SOLID SHAFT PIER ON CONCRETE SPREAD FOOTING FOUNDATION SCOUR EVALUATION Bridge has unknown foundations. Risk of scour cannot be determined. The bridge shall be monitored for distress during significant flood events. Monitor bridge in lieu of installing scour countermeasures. **INSPECTION PROCEDURES** [] BridgeWatch Alert What Initiated the Call-out Inspection? [1 TDOT District or Local Maintenance Personnel [] THP or Local Law Enforcement Personnel [] Other: Things to check on a bridge during floods: [] - Span movement - horizontally as well as vertically 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck. 2. Check for plumb of piers or bents. [] - Check for embankment erosion [] - Check for drift build-up on piers or bents [] - Check pier exposure, if possible, and compare to previous inspection [] - Review the latest bridge inspection report versus current field conditions If Closure is recommended: [] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded. [] - Contact: (1) District Maintenance Supervisor (if bridge is State maintained) (2) City or County Highway Maintenance Official (if bridge is not State maintained) (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate

PUBLICATION DATE

(4) TDOT Regional Bridge Engineer

by a TDOT bridge inspection team.

[] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route. 	e District maintenance or local highway maintenance dge on the selected detour route shall be checked
[] - The bridge can be re-opened only after a TDOT units and they are determined to be structurall	bridge inspection team checks the substructure y stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
REGION BRIDGE ENGINEER	(615) 476-8860
DISTRICT MAINTENANCE SUPERVISOR	(931) 205-6399
TENNESSEE HIGHWAY PATROL	(615) 741-3181
[] - Summarize and submit findings from the inspection of the report shall include the date and time of the as appropriate, photographs of the bridge and scouring has occurred, the report shall also be	e inspection, a brief summary of findings and, stream channel measurements. If significant
COMMENTS:	
Suggested List of Equipment to conduct the Inspecti	on:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist	
Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	no printed with the fellowing managers.
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	
SAFETY HAZARD KEEP AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)