HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 220A1270003

BRIDGE OWNER: DICKSON COUNTY

ROAD NAME: WEST FIELD RD

CROSSING: LITTLE JONES CREEK

LATITUDE:: N 36.13015 DEGREES

LONGITUDE: W 87.37717 DEGREES

COUNTY: DICKSON
ROUTE: 0A224
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.11
YEAR BUILT: 1986

2011	1011052: 11 01:01111	•		12/11/20121. 1900
		TYPE OF SUPE	ERSTRUCTURE -	
MAIN SPAN:	PRESTRESSED CONCRETE CONTIL STRINGER/MULTI-BEAM OR GIRDE		APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUE	STRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	HT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS: CONCRETE SOLID SHAFT PIER ON CONCRETE SPREAD FOOTING FOUNDATION				UNDATION
		SCOUR EV	ALUATION -	
	inknown foundations. Risk of sco icant flood events. Monitor bridge			bridge shall be monitored for distress termeasures.
		INSPECTION I	PROCEDURES -	
What Initiated the Call-out Inspection?		[] Bridge	Watch Alert	
		[] TDOT	District or Loca	al Maintenance Personnel
		[] THP o	r Local Law Ent	forcement Personnel
		[] Other:		
Things to c	heck on a bridge during floods	<u>s:</u>		
	movement - horizontally as w Check displacement / deflectio		-	e rails and outer edge of bridge deck.
	Check for plumb of piers or be	nts.		
	k for embankment erosion			
	k for drift build-up on piers or			
	k pier exposure, if possible, ar	-		
[] - Revie	ew the latest bridge inspection	report versus	s current field c	onditions
lf Closure is	recommended:			
			4:1 buides is see	and and preventy aloned by District
Coun temp	ty or City Maintenance Persor	nnel. Use Barr rists to stay of	icade Tape, traf	eured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if	bridge is State	maintained)
	(2) City or County Highwa	y Maintenanc	e Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or lo	cal law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engineer		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



	officials in establishing a detour route. Any bridg prior to signing the detour route.	e on the selected detour route shall be checked			
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.				
2	CONTACT PERSONNEL:	TELEPHONE NUMBER:			
C	COUNTY MAYOR'S OFFICE	(615) 789-7003			
H	HWY. CHIEF ADMINISTRATOR'S OFFICE	(615) 446-2638			
C	COUNTY SHERIFF'S OFFICE	(615) 789-4130			
T a	 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. 				
СОММЕ	NTS:				
Sugges	sted List of Equipment to conduct the Inspection	<u>:</u>			
Latest	Bridge Inspection Report				
Scour I	POA Report with the above Checklist				
Bridge	Design Plans, if available				
Tape m	neasure with weight				
Plumb	bob				
Range					
A 1000	Foot Roll of yellow Polyethylene Barricade Tape				
		MAV			

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24