HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 23002270009 COUNTY: DYER
BRIDGE OWNER: STATE OF TENNESSEE ROUTE: SR211

ROAD NAME: SR211

CROSSING: REEDS CREEK

LATITUDE:: N 36.17856 DEGREES LONGITUDE: W 89.21639 DEGREES

ROUTE: SR211
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 14.92
YEAR BUILT: 1928

LON	NGHODE. W 69.21639 DEGREES	TEAR BOILT. 1920
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	CONCRETE SPILL THROUGH ABUT	MENT ON TIMBER PILE FOUNDATION
BENTS:	NOT APPLICABLE	
PIERS:	CONCRETE HAMMERHEAD PIER O	N TIMBER PILE FOUNDATION
		SCOUR EVALUATION
	our critical; bridge foundations de stalled and is in good condition.	etermined to be unstable for calculated scour conditions. Rip-rap protection
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
	·	[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to c	<u>heck on a bridge during floods</u>	<u>S:</u>
[] - Span	movement - horizontally as w	ell as vertically
1. C	Check displacement / deflectio	n along curb line, both bridge rails and outer edge of bridge deck.
2. 0	Check for plumb of piers or be	nts.
[] - Chec	k for embankment erosion	
[] - Chec	k for drift build-up on piers or	bents
[] - Chec	k pier exposure, if possible, ar	nd compare to previous inspection
[] - Revie	ew the latest bridge inspection	report versus current field conditions
lf Claavina ia		
	recommended:	
Coun temp	ity or City Maintenance Persor	cross road until bridge is secured and properly closed by District, anel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	vill work with State District maintenance or local highway maintenance our route. Any bridge on the selected detour route shall be checked ute.		
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVI	SOR (731) 571-8883		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to con	nduct the Inspection:		
Latest Bridge Inspection Report			
Scour POA Report with the above C	Checklist		
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
	lene Barricade Tape printed with the following message:		
SAFET	Y HAZARD KEEP AWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24