Rev. 07-24-15		IWAY BRIDGE SCOUR	TN TDOT Department of Transportation			
BRIDGE ID NUMBER: 23101550001			COUNTY: DYER			
BRIDGE	OWNER: STATE OF TENNESSEE		ROUTE: 10155			
ROAD NAME: 1155			SPECIAL CASE: 0			
CF	ROSSING: MISSISSIPPI RIVER		COUNTY SEQUENCE: 1			
LA	TITUDE:: N 36.11833 DEGREES	5	LOG MILE: 0.00			
LON	NGITUDE: W 89.61500 DEGREES	5	YEAR BUILT: 1975			
		TYPE OF SUPERSTRUCTURE				
MAIN SPAN:	STEEL CONTINUOUS - TRUSS - TH	RU APPR. SPAN:	PRESTRESSED CONCRETE CONTINUOUS - STRINGER/MULTI-BEAM OR GIRDER			
		TYPE OF SUBSTRUCTURE				
ABUTMENTS:	CONCRETE STUB ABUTMENT ON S	STEEL PILE FOUNDATION				
BENTS:	BENTS: CONCRETE COLUMN THREE POST BENT ON STEEL PILE FOUNDATION					
PIERS:	PIERS: CONCRETE SOLID SHAFT PIER ON CONCRETE PILE FOUNDATION					
		SCOUR EVALUATION				
	our critical; bridge foundations de sures are installed but they are r	etermined to be unstable for ca leeded.	Iculated scour conditions. No scour			
		INSPECTION PROCEDURES				
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert				
		[] TDOT District or Local Maintenance Personnel				
		[] THP or Local Law Enforcement Personnel				

[] Other: _____

Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
 - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
 - 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
 - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
 - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
 - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBI	LIC	ATI	ON C	DATE

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
REGION BRIDGE ENGINEER	(731) 234-9561
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883
TENNESSEE HIGHWAY PATROL	(901) 543-6256

[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

COMMENTS: _____

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

Range Pole

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)

PUBLICATION DATE