## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 23SR0200017 COUNTY: DYER ROUTE: SR104 BRIDGE OWNER: STATE OF TENNESSEE ROAD NAME: SR104 SPECIAL CASE: 0 CROSSING: BRANCH COUNTY SEQUENCE: 1

	TITUDE:: N 36.03608 DEGREES GITUDE: W 89.42636 DEGREES		
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE - ARCH - DECK	APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE ARCH TYPE ON STEEL	PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
		our cannot be determined. The bridge shall be monitored for distress ction has been installed and is in good condition.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	•	[ ] TDOT District or Local Maintenance Personnel	
		[ ] THP or Local Law Enforcement Personnel	
		[ ] Other:	
1. 0 2. 0 [ ] - Checl [ ] - Checl	check for plumb of piers or bei k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, ar	n along curb line, both bridge rails and outer edge of bridge deck. nts.	
f Closure is	recommended:		
Coun temp	ty or City Maintenance Person	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[ ] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)		
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer	
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



of	ne bridge inspection team will work with State Dis ficials in establishing a detour route. Any bridge ior to signing the detour route.	strict maintenance or local highway maintenance on the selected detour route shall be checked	
[ ] -Th ur	- The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CC	ONTACT PERSONNEL:	TELEPHONE NUMBER:	
RE	GION BRIDGE ENGINEER	(731) 234-9561	
DIS	STRICT MAINTENANCE SUPERVISOR	(731) 571-8883	
TE	NNESSEE HIGHWAY PATROL	(901) 543-6256	
The as	<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.</li> <li>The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>		
COMMEN	TS:		
	ed List of Equipment to conduct the Inspection:		
	ridge Inspection Report  OA Report with the above Checklist		
	Design Plans, if available		
_	easure with weight		
Plumb b	ob		
Range P	ole		
A 1000 F	oot Roll of yellow Polyethylene Barricade Tape p	rinted with the following message:	
	SAFETY HAZARD KEED AWA	\V	

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24