HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 23SR0200023 COUNTY: DYER
BRIDGE OWNER: STATE OF TENNESSEE ROUTE: SR104

ROAD NAME: SR104 SPECIAL CASE: 0

CROSSING: BRANCH

LATITUDE:: N 36.03419 DEGREES
LONGITUDE: W 89.43933 DEGREES

SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 13.71
YEAR BUILT: 1940

LON	NGITUDE: W 89.43933 DEGREE	S	YEAR BUILT: 1940		
		TYPE OF SUPERSTRUCTURE			
MAIN SPAN:	CONCRETE - SLAB	APPR. SPAN:	NOT APPLICABLE		
		TYPE OF SUBSTRUCTURE			
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTM	ENT ON CONCRETE SPREAD FOOTI	NG FOUNDATION		
BENTS:	NOT APPLICABLE				
PIERS:	NOT APPLICABLE				
		SCOUR EVALUATION			
•	unknown foundations. Risk of so icant flood events. Rip-rap prote		bridge shall be monitored for distress in good condition.		
		- INSPECTION PROCEDURES -			
What Initiat	ed the Call-out Inspection?	[] BridgeWatch Alert			
		[] TDOT District or Loca	al Maintenance Personnel		
		[] THP or Local Law En	forcement Personnel		
		[] Other:			
Things to c	heck on a bridge during flood	s:			
_	movement - horizontally as v				
		•	e rails and outer edge of bridge deck.		
	Check for plumb of piers or be		o rano ana cato. cago er zinago acom		
	k for embankment erosion				
	k for drift build-up on piers or	bents			
	k pier exposure, if possible, a		ection		
[] - Revie] - Review the latest bridge inspection report versus current field conditions				
lf Clasura is	recommended:				
			are down a manager along day. District		
Coun temp	nty or City Maintenance Perso	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may		
•	ct: (1) District Maintenance Supervisor(if bridge is State maintained)				
	` '		ridge is not State maintained)		
	` ' '	Patrol and/or local law enforce	,		
	(4) TDOT Regional Bridge	e Engineer			
	idge should remain closed until the water recedes and a daylight visual inspection is made				

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any brid	lge on the selected detour route shall be checked		
	oridge can be re-opened only after a TDOT bridge inspection team checks the substructure and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(731) 234-9561		
DISTRICT MAINTENANCE SUPERVISOR	(731) 571-8883		
TENNESSEE HIGHWAY PATROL	(901) 543-6256		
The report shall include the date and time of the as appropriate, photographs of the bridge and s scouring has occurred, the report shall also be COMMENTS:	tream channel measurements. If significant copied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspection	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
SAFETY HAZARD KEEP A	AWAY		

TDOT radio directory (State Personnel only)

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape