## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 24015570003 BRIDGE OWNER: FAYETTE COUNTY ROAD NAME: YUM YUM RD CROSSING: BRANCH

LATITUDE" N 35 38172 DEGREES

COUNTY: FAYETTE ROUTE: 01557 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 6.71

LON	IGITUDE: W 89.35419 DEGREE	S	YEAR BUILT: 2020
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FO	JNDATION	
BENTS:	TIMBER PILE BENT ON PILE FOUN	IDATION	
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION -	
event. Deter		riprap should be reported to TI	the risk of bridge failure during a flood DOT for assessment. Rip-rap protection has system are needed.
		<ul> <li>INSPECTION PROCEDURES</li> </ul>	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
			al Maintenance Personnel
		[ ] THP or Local Law En	
		[ ] Other:	
[ ] - Span 1. C 2. C [ ] - Chec [ ] - Chec	heck on a bridge during flood movement - horizontally as we check displacement / deflection check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a ew the latest bridge inspection	vell as vertically on along curb line, both bridg ents. bents nd compare to previous insp	
lf Closure is	recommended:		
Coun temp	ity or City Maintenance Perso	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[ ] - Conta	act: (1) District Maintenance S	maintained )	
	(2) City or County Highwa	ay Maintenance Official ( if b	ridge is not State maintained )
	(3) Tennessee Highway F	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer	
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked		
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(901) 465-5202		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 465-5232		
COUNTY SHERIFF'S OFFICE	(901) 465-3456		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspe	ection:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade			
SAFETY HAZARD KE	EP AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24