## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 240A0060005

BRIDGE OWNER: FAYETTE COUNTY

ROAD NAME: FIELDS DR

CROSSING: BLACK ANKLE CREEK
LATITUDE:: N 35.27289 DEGREES
LONGITUDE:: W 89.55992 DEGREES

COUNTY: FAYETTE
ROUTE: 0A006
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 1.81
YEAR RUILT: 1994

LOI	NGHODE: W 69.33992 DEGREES	1 LAN BOILT. 1994
		TYPE OF SUPERSTRUCTURE
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	MASONRY OR CONCRETE BLOCK	ABUTMENTS ON TIMBER PILE FOUNDATION
BENTS:	TIMBER PILE BENT ON PILE FOUN	DATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
Bridge has I	unknown foundations. Risk of so	our cannot be determined. The bridge shall be monitored for distress
		e in lieu of installing scour countermeasures.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert
		[ ] TDOT District or Local Maintenance Personnel
		THP or Local Law Enforcement Personnel
		[ ] Other:
Things to c	heck on a bridge during flood:	<u>s:</u>
[ ] - Span	n movement - horizontally as w	ell as vertically
	•	n along curb line, both bridge rails and outer edge of bridge deck.
	Check for plumb of piers or be	
	k for embankment erosion	
	k for drift build-up on piers or	bents
	• •	nd compare to previous inspection
Review the latest bridge inspection report versus current field conditions		
	3	
<u>If Closure is</u>	s recommended:	
Cour temp	nty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may
[ ] - Contact: (1) District Maintenanc		Supervisor ( if bridge is State maintained )
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer
	Bridge should remain closed u TDOT bridge inspection team.	ntil the water recedes and a daylight visual inspection is made

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[ ] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Any bri	idge on the selected detour route shall be checked		
	dge can be re-opened only after a TDOT bridge inspection team checks the substructure nd they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(901) 465-5202		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 465-5232		
COUNTY SHERIFF'S OFFICE	(901) 465-3456		
The report shall include the date and time of th as appropriate, photographs of the bridge and scouring has occurred, the report shall also be	stream channel measurements. If significant copied to Bridge Inspection Headquarters.		
Suggested List of Equipment to conduct the Inspect	ion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:		
SAFETY HAZARD KEEP	AWAY		

**TDOT radio directory (State Personnel only)** 

Traffic Cones - Minimum of four (4)

A Barricade Tape Dispenser with serrated cutter

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

A roll of Duct Tape