HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 24S80790001
BRIDGE OWNER: FAYETTE COUNTY
ROAD NAME: SLAYDEN RD
CROSSING: SANDY CREEK

COUNTY: FAYETTE
ROUTE: 00845
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.27
VEAR BUILT: 1938

	TITUDE:: N 35.04922 DEGREE: GITUDE: W 89.44089 DEGREE:	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/ GIRDER	TYPE OF SUPERSTRUCTURE MULTI-BEAM OR APPR. SPAN: NOT APPLICABLE
		TYPE OF SUBSTRUCTURE
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FOL	
BENTS:	TIMBER PILE BENT ON PILE FOUN	IDATION
PIERS:	NOT APPLICABLE	
		SCOUR EVALUATION
	our critical; bridge foundations desures are installed but they are i	etermined to be unstable for calculated scour conditions. No scour needed.
		INSPECTION PROCEDURES
What Initiated the Call-out Inspection?		[] BridgeWatch Alert
		[] TDOT District or Local Maintenance Personnel
		[] THP or Local Law Enforcement Personnel
		[] Other:
Things to cl	neck on a bridge during flood	<u>S:</u>
	movement - horizontally as w	•
	-	on along curb line, both bridge rails and outer edge of bridge deck.
	check for plumb of piers or be	nts.
	k for embankment erosion	hauta
	k for drift build-up on piers or	
		nd compare to previous inspection
[] - Kevie	w the latest bridge inspection	report versus current field conditions
f Closure is	recommended:	
Coun tempe	ty or City Maintenance Perso	ncross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may.
[] - Conta	nct: (1) District Maintenance S	Supervisor (if bridge is State maintained)
	(2) City or County Highwa	ay Maintenance Official (if bridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.	

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	tate District maintenance or local highway maintenance bridge on the selected detour route shall be checked	
] - The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:	
COUNTY MAYOR'S OFFICE	(901) 465-5202	
HWY. CHIEF ADMINISTRATOR'S OFFICE	(901) 465-5232	
COUNTY SHERIFF'S OFFICE	(901) 465-3456	
- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.		
COMMENTS:		
Suggested List of Equipment to conduct the Inspe	ection:	
Latest Bridge Inspection Report		
Scour POA Report with the above Checklist		
Bridge Design Plans, if available		
Tape measure with weight		
Plumb bob		
Range Pole		
A 1000 Foot Roll of yellow Polyethylene Barricade	Tape printed with the following message:	
SAFETY HAZARD KEE	EP AWAY	

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19