HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 26S44040001

BRIDGE OWNER: FRANKLIN COUNTY

ROAD NAME: ROARKS COVE RD

CROSSING: DICK CREEK

LATITUDE:: N 35.24932 DEGREES
LONGITUDE: W 85.93407 DEGREES

COUNTY: FRANKLIN
ROUTE: 01103
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 4.95
YEAR BUILT: 1940

LON	IGITUDE: W 85.93407 DEGREES	YEAR BUILT: 1940	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	TYPE OF SUPERSTRUCTURE R GIRDER APPR. SPAN: NOT APPLICABLE	
A DU ITA IEN ITO		TYPE OF SUBSTRUCTURE	
	S: CONCRETE FULL HEIGHT ABUTMENT ON CONCRETE SPREAD FOOTING FOUNDATION		
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION ————————————————————————————————————	
•		our cannot be determined. The bridge shall be monitored for distress in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
	•	TDOT District or Local Maintenance Personnel	
		THP or Local Law Enforcement Personnel	
		[] Other:	
Things to c	heck on a bridge during floods	<u>:</u>	
[] - Snan	movement - horizontally as w	ell as vertically	
	•	n along curb line, both bridge rails and outer edge of bridge deck.	
	Check for plumb of piers or be		
	k for embankment erosion		
[] - Check for drift build-up on piers or bents			
[] - Check pier exposure, if possible, and compare to previous inspection			
[] - Review the latest bridge inspection report versus current field conditions			
[]	o .a.oo. bagoopooo		
If Closure is	recommended:		
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nel. Use Barricade Tape, traffic cones and/or traffic flares as ists to stay off of the bridge until such time as the bridge may	
[] - Conta	act: (1) District Maintenance S	upervisor (if bridge is State maintained)	
	(2) City or County Highwa	y Maintenance Official (if bridge is not State maintained)	
	(3) Tennessee Highway Pa	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	••••	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route. 	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 967-2905		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 967-2755		
COUNTY SHERIFF'S OFFICE	(931) 967-2331		
[] - Summarize and submit findings from the inspect The report shall include the date and time of the as appropriate, photographs of the bridge and st scouring has occurred, the report shall also be c	inspection, a brief summary of findings and, ream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>n:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
SAFETY HAZARD KEEP A	WAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24