## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 27015850011 COUNTY: GIBSON BRIDGE OWNER: GIBSON COUNTY ROUTE: 01585 SPECIAL CASE: 0 ROAD NAME: SALEM CHURCH RD. COUNTY SEQUENCE: 1 CROSSING: RUTHERFORD FK OF OBION R LATITUDE:: **N** 35.96197 DEGREES LOG MILE: 1.73 LONGITUDE: W 88.73367 YEAR BUILT: 1987 DEGREES TYPE OF SUPERSTRUCTURE PRESTRESSED CONCRETE - BOX BEAM OR APPR. SPAN: NOT APPLICABLE MAIN SPAN-**GIRDERS - SINGLE OR SPREAD**  TYPE OF SUBSTRUCTURE ABUTMENTS: CONCRETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION BENTS: **NOT APPLICABLE** PIERS: CONCRETE HAMMERHEAD PIER ON CONCRETE PILE FOUNDATION **SCOUR EVALUATION** Bridge is scour critical; bridge foundations determined to be unstable for calculated scour conditions. No scour countermeasures are installed but they are needed. INSPECTION PROCEDURES What Initiated the Call-out Inspection? [ ] BridgeWatch Alert [ ] TDOT District or Local Maintenance Personnel [ 1 THP or Local Law Enforcement Personnel [ ] Other: Things to check on a bridge during floods: [ ] - Span movement - horizontally as well as vertically

- - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.
  - 2. Check for plumb of piers or bents.
- [ ] Check for embankment erosion
- [ ] Check for drift build-up on piers or bents
- [ ] Check pier exposure, if possible, and compare to previous inspection
- [ ] Review the latest bridge inspection report versus current field conditions

### If Closure is recommended:

- [ ] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
  - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [ ] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

#### **PUBLICATION DATE**

# HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	ate District maintenance or local highway maintenance oridge on the selected detour route shall be checked
[ ] - The bridge can be re-opened only after a TDC units and they are determined to be structural	OT bridge inspection team checks the substructure ally stable.
CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(731) 855-7611
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 855-7684
COUNTY SHERIFF'S OFFICE	(731) 855-1121
	the inspection, a brief summary of findings and, d stream channel measurements. If significant
COMMENTS:	
Suggested List of Equipment to conduct the Inspec	ction:
Latest Bridge Inspection Report	
Scour POA Report with the above Checklist Bridge Design Plans, if available	
Tape measure with weight	
Plumb bob	
Range Pole	
A 1000 Foot Roll of yellow Polyethylene Barricade 1	Tape printed with the following message:
SAFETY HAZARD KEE	

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24