## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 270A9730001
BRIDGE OWNER: GIBSON COUNTY
ROAD NAME: ARNOLD RD
CROSSING: BR.OF BUCK CREEK

LATITUDE:: N 35.95753 DEGREES
LONGITUDE: W 89.11475 DEGREES

COUNTY: GIBSON
ROUTE: 0A973
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.15
YEAR BUILT: 1988

LON	NGITUDE: W 89.11475 DEGREE	S	YEAR BUILT: 1988	
		TYPE OF SUPERSTRUCTURE =		
MAIN SPAN:	CONCRETE - CHANNEL BEAM	APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE -		
ABUTMENTS:	TIMBER CAP ON TIMBER PILE FO	JNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
	unknown foundations. Risk of so icant flood events. Monitor bridg		bridge shall be monitored for distress termeasures.	
		- INSPECTION PROCEDURES -		
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert		
		[ ] TDOT District or Loca	Il Maintenance Personnel	
		[ ] THP or Local Law En	orcement Personnel	
		[ ] Other:		
_	heck on a bridge during flood			
	movement - horizontally as w Check displacement / deflection	· ·	e rails and outer edge of bridge deck.	
2. 0	Check for plumb of piers or be	ents.		
[ ] - Chec	k for embankment erosion			
[ ] - Chec	k for drift build-up on piers or	bents		
[ ] - Chec	k pier exposure, if possible, a	nd compare to previous inspe	ection	
[ ] - Revie	ew the latest bridge inspection	n report versus current field c	onditions	
lf Closure is	recommended:			
Coun temp	nty or City Maintenance Perso	nnel. Use Barricade Tape, trat rists to stay off of the bridge	eured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may	
[ ] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highwa	ay Maintenance Official ( if br	idge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer		
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.			

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any brid prior to signing the detour route.</li> </ul>	e District maintenance or local highway maintenance lige on the selected detour route shall be checked		
<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>			
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 855-7611		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 855-7684		
COUNTY SHERIFF'S OFFICE	(731) 855-1121		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection  Latest Bridge Inspection Report	on:		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap	pe printed with the following message:		
SAFETY HAZARD KEEP /	AWAY		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)