## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



BRIDGE ID NUMBER: 280A0340001 BRIDGE OWNER: GILES COUNTY ROAD NAME: HAMS CR RD CROSSING: HAM'S CREEK

> I ATITUDE" N 35 25722 DEGREES

COUNTY: GILES ROUTE: 0A034 SPECIAL CASE: 0 COUNTY SEQUENCE: 1 LOG MILE: 4.59

LON	NGITUDE: W 87.16438 DEGREE	5	YEAR BUILT: 1940	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	CONCRETE - TEE BEAM	APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMI	ENT ON CONCRETE SPREAD FOOTI	NG FOUNDATION	
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
•	unknown foundations. Risk of sc icant flood events. Monitor bridg		bridge shall be monitored for distress termeasures.	
		- INSPECTION PROCEDURES -		
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert		
		[ ] TDOT District or Loca	al Maintenance Personnel	
		[ ] THP or Local Law Ent	forcement Personnel	
		[ ] Other:		
[ ] - Span 1. C 2. C [ ] - Chec [ ] - Chec	heck on a bridge during flood movement - horizontally as we Check displacement / deflection Check for plumb of piers or be the k for embankment erosion the k for drift build-up on piers or the k pier exposure, if possible, a the way the latest bridge inspection	vell as vertically on along curb line, both bridge nts. bents nd compare to previous inspe		
<u>lf Closure is</u>	recommended:			
Coun temp	nty or City Maintenance Perso	nnel. Use Barricade Tape, trat rists to stay off of the bridge	eured and properly closed by District, ific cones and/or traffic flares as until such time as the bridge may	
[ ] - Conta	ct: (1) District Maintenance Supervisor (if bridge is State maintained)			
	(2) City or County Highwa	ay Maintenance Official ( if br	idge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforce	ment Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer		
	Bridge should remain closed เ TDOT bridge inspection team.		daylight visual inspection is made	

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



<ul> <li>The bridge inspection team will work with State officials in establishing a detour route. Any bridge prior to signing the detour route.</li> </ul>	District maintenance or local highway maintenance ge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 363-5300		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 363-1635		
COUNTY SHERIFF'S OFFICE	(931) 363-2460		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.     </li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspectio  Latest Bridge Inspection Report	<u>n:</u>		
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tap			
	1A/ A 🗸		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24