HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



COUNTY: GREENE

BRIDGE ID NUMBER: 30025170001
BRIDGE OWNER: GREENE COUNTY
ROAD NAME: OLD ASHEVILLE HWY
CROSSING: MUD CREEK

LATITUDE:: N 36.07582 DEGREES LONGITUDE: W 82.83675 DEGREES

ROUTE: 02517
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.90
YEAR BUILT: 1950

		TVDE	OF SUPERSTRUCTURE =	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OR			NOT APPLICABLE
W/ (114 O1 7 (14.	OTELL OTHINGLIAMOLIT BEAM OF	CIICDE	70 7 10. 01 700	NOT ALL EIGABLE
		TYPE	OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTMEN	IT ON U	INKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE			
PIERS:	CONCRETE SOLID SHAFT PIER ON	UNKNO	WN FOUNDATION	
		so	OUR EVALUATION -	
	inknown foundations. Risk of sco icant flood events. Monitor bridge			bridge shall be monitored for distress termeasures.
		INSPE	ECTION PROCEDURES =	
What Initiate	ed the Call-out Inspection?	r 1	BridgeWatch Alert	
		11	<u> </u>	Il Maintenance Personnel
		11	THP or Local Law Enf	
		1 1		
Things to cl	heck on a bridge during floods	<u>.</u>		
1. 0 2. 0 [] - Checl [] - Checl	movement - horizontally as we check displacement / deflection check for plumb of piers or bench for embankment erosion k for drift build-up on piers or k pier exposure, if possible, and the latest bridge inspection	along ts. pents d com	g curb line, both bridge pare to previous inspe	
f Closure is	recommended:			
Coun temp	ty or City Maintenance Person	nel. Us	se Barricade Tape, traf	ured and properly closed by District, fic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	ıpervi	sor (if bridge is State	maintained)
	(2) City or County Highway	/ Main	tenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	trol ar	nd/or local law enforce	ment Officers as appropriate
	(4) TDOT Regional Bridge	Engin	eer	
	Bridge should remain closed un FDOT bridge inspection team.	til the	water recedes and a c	daylight visual inspection is made

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	will work with State District maintenance or local highway maintenance stour route. Any bridge on the selected detour route shall be checked oute.				
[] - The bridge can be re-opened units and they are determined	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 				
CONTACT PERSONNEL:	TELEPHONE NUMBER:				
COUNTY MAYOR'S OFFICE	(423) 798-1766				
HWY. CHIEF ADMINISTRATOR'S O	FFICE (423) 798-1747				
COUNTY SHERIFF'S OFFICE	(423) 798-1800				
The report shall include the cas appropriate, photographs	- Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.				
COMMENTS:					
Suggested List of Equipment to co	onduct the Inspection:				
Latest Bridge Inspection Report	Observices				
Scour POA Report with the above	Checklist				
Bridge Design Plans, if available					
Tape measure with weight Plumb bob					
Range Pole					
<u> </u>	ylene Barricade Tape printed with the following message:				
	TV HAZADD KEED AWAY				

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24