HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 300A1680001
BRIDGE OWNER: GREENE COUNTY
ROAD NAME: DELTA VALLEY RD
CROSSING: SAYLOR CREEK

LATITUDE:: N 36.25925 DEGREES LONGITUDE: W 82.89377 DEGREES

COUNTY: GREENE
ROUTE: 0A168
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.12
YEAR BUILT: 1999

20.	10.1100E. 11 02.00077 DEGREES			12/11/20121. 1000
		TYPE OF SUPE	RSTRUCTURE -	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	R GIRDER	APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUB	STRUCTURE =	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME			
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVA		
	ınknown foundations. Risk of sco icant flood events. Monitor bridge			bridge shall be monitored for distress ntermeasures.
		INSPECTION P	ROCEDURES -	
What Initiated the Call-out Inspection?		[] Bridge\	Watch Alert	
				al Maintenance Personnel
				forcement Personnel
1. C 2. C [] - Chec	movement - horizontally as w Check displacement / deflectio Check for plumb of piers or bea k for embankment erosion k for drift build-up on piers or	n along curb li		e rails and outer edge of bridge deck.
	k pier exposure, if possible, ar		nrevious insn	ection
	ew the latest bridge inspection	-		
[]	on the latest bridge mepochen	roport vorodo		
lf Closure is	recommended:			
Coun temp	nty or City Maintenance Persor	nnel. Use Barrio rists to stay off	cade Tape, tra	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance S	Supervisor (if	bridge is State	maintained)
	(2) City or County Highwa	y Maintenance	Official (if b	ridge is not State maintained)
	(3) Tennessee Highway Pa	atrol and/or loc	al law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	e District maintenance or local highway maintenance dge on the selected detour route shall be checked			
	 The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable. 			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(423) 798-1766			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 798-1747			
COUNTY SHERIFF'S OFFICE	(423) 798-1800			
[] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.				
COMMENTS:				
Suggested List of Equipment to conduct the Inspect	ion:			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole				
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:			
SAFETY HAZARD KEEP				

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)