HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 30S23910003

BRIDGE OWNER: STATE OF TENNESSEE
ROAD NAME: CHUCKEY PIKE
CROSSING: NOLICHUCKY RIVER
LATITUDE:: N 36.20470 DEGREES

COUNTY: GREENE
ROUTE: SR351
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 16.17
YEAR BUILT: 1994

LON	IGITUDE: W 82.68273 DEGREE	5	YEAR BUILT: 1994
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE CONT STRINGER/MULTI-BEAM OR GIRDI		NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE STUB ABUTMENT ON	CONCRETE PILE FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE HAMMERHEAD PIER O	ON CONCRETE PILE FOUNDATION	
		SCOUR EVALUATION	
			is imminent. Bridge is closed to traffic. Rippair or replacement of the protection system
		INSPECTION PROCEDURES -	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
1. C 2. C [] - Chec [] - Chec [] - Chec	movement - horizontally as we check displacement / deflection check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a sew the latest bridge inspection	on along curb line, both bridg ints. bents nd compare to previous insp	
If Closure is	recommended:		
Coun temp	at bridge with vehicle pulled across road until bridge is secured and properly closed by District, nty or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as porary measures to warn motorists to stay off of the bridge until such time as the bridge may properly closed and barricaded.		
[] - Conta	act: (1) District Maintenance S	Supervisor (if bridge is State	e maintained)
	(2) City or County Highwa	ay Maintenance Official (if b	ridge is not State maintained)
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge	e Engineer	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance idge on the selected detour route shall be checked		
	ge can be re-opened only after a TDOT bridge inspection team checks the substructure d they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
REGION BRIDGE ENGINEER	(865) 712-8292		
DISTRICT MAINTENANCE SUPERVISOR	(423) 202-5393		
TENNESSEE HIGHWAY PATROL	(423) 348-6144		
The report shall include the date and time of the as appropriate, photographs of the bridge and scouring has occurred, the report shall also be	stream channel measurements. If significant e copied to Bridge Inspection Headquarters.		
COMMENTS:			
Suggested List of Equipment to conduct the Inspect	ion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	ape printed with the following message:		
SAFETY HAZARD KEEP			
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)