HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 310A0230003
BRIDGE OWNER: GRUNDY COUNTY
ROAD NAME: HUBBARDS COVE RD.

CROSSING: BRANCH

LATITUDE:: N 35.49060 DEGREES LONGITUDE: W 85.85183 DEGREES

COUNTY: GRUNDY
ROUTE: 0A023
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.92

LON	NGITUDE: W 85.85183 DEGREES		YEAR BUILT: 1970
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM OF	TYPE OF SUPERSTRUCTURE = R GIRDER APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE =	
ARI ITMENTS:	CONCRETE FULL HEIGHT ABUTMEN		
BENTS:			
PIERS:	NOT APPLICABLE		
		OCCUP EVALUATION	
5.1		SCOUR EVALUATION =	
•	inknown foundations. Risk of scolicant flood events. Monitor bridge		bridge shall be monitored for distress termeasures.
		INSPECTION PROCEDURES =	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
		[] TDOT District or Loca	al Maintenance Personnel
		[] THP or Local Law En	forcement Personnel
		[] Other:	
Things to c	<u>heck on a bridge during floods</u>	<u>:</u>	
	movement - horizontally as we	•	
	·		e rails and outer edge of bridge deck.
	Check for plumb of piers or ben	ts.	
	k for embankment erosion		
	k for drift build-up on piers or b		
	k pier exposure, if possible, an		
[] - Revie	ew the latest bridge inspection	report versus current field c	onditions
If Closure is	recommended:		
		roce road until bridgo is soo	cured and properly closed by District,
Coun temp	nty or City Maintenance Person	nel. Use Barricade Tape, traf	ific cones and/or traffic flares as until such time as the bridge may
[] - Conta	act: (1) District Maintenance Su	upervisor (if bridge is State	maintained)
	(2) City or County Highway	/ Maintenance Official (if br	idge is not State maintained)
	(3) Tennessee Highway Pa	trol and/or local law enforce	ement Officers as appropriate
	(4) TDOT Regional Bridge		-
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



	te District maintenance or local highway maintenance ridge on the selected detour route shall be checked		
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(931) 692-3718		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(931) 592-3751		
COUNTY SHERIFF'S OFFICE	(931) 692-3466		
] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.			
COMMENTS:			
Suggested List of Equipment to conduct the Inspec	tion:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade T			
SAFETY HAZARD KEEF	PAWAY		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24