Rev. 07-24-15	-	HWAY BRIDGE SCOUR N OF ACTION REPORT	TN TDOT Department of Transportation
BRIDGE ID NUMBER: 33022190005			COUNTY: HAMILTON
BRIDGE OWNER: HAMILTON COUNTY			ROUTE: 02219
ROAD NAME: BIG SODDY CREEK			SPECIAL CASE: 0
CR	OSSING: BIG POSSUM CREEK		COUNTY SEQUENCE: 1
LA	TITUDE:: N 35.34137 DEGREE	S	LOG MILE: 5.72
LON	GITUDE: W 85.13467 DEGREE	S	YEAR BUILT: 1965
		- TYPE OF SUPERSTRUCTURE -	
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM	OR GIRDER APPR. SPAN:	NOT APPLICABLE
J.		- TYPE OF SUBSTRUCTURE -	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTM	ENT ON CONCRETE SPREAD FOOTI	
BENTS:			
PIERS:			
PIERS.	NOT APPLICABLE		
		- SCOUR EVALUATION -	
during signifi		ection was installed but it has fai	bridge shall be monitored for distress led and is now ineffective. Major repair or
		- INSPECTION PROCEDURES -	
What Initiate	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
		[ ] TDOT District or Loca	I Maintenance Personnel
		[ ] THP or Local Law End	orcement Personnel

## Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
  - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.

[] Other:

- 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [ ] Review the latest bridge inspection report versus current field conditions

## If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor (if bridge is State maintained)
  - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [ ] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

PUBLICATION DA	TΕ
----------------	----

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	TELEPHONE NUMBER:
COUNTY MAYOR'S OFFICE	(423) 209-6100
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 855-6106
PUBLIC WORKS DIRECTOR	(423) 209-7899
COUNTY SHERIFF'S OFFICE	(423) 209-7000

[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

## COMMENTS:

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

**Range Pole** 

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

## SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)** 

PUBLICATION DATE

07-Nov-24