## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 330A7830001

BRIDGE OWNER: CITY OF CHATTANOOGA

ROAD NAME: RIVERSIDE DR CROSSING: CITICO CREEK

LATITUDE:: N 35.05288 DEGREES
LONGITUDE: W 85.28697 DEGREES

COUNTY: HAMILTON
ROUTE: 0A783
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.10

YEAR BUILT: 1930

		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	CONCRETE CONTINUOUS - TEE B	EAM APPR. SPAN: NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTM	ENT ON UNKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	TWO ROWS OF TIMBER PILES WI	TH A COMMON CAP ON UNKNOWN FOUNDATION	
		SCOUR EVALUATION	
		our cannot be determined. The bridge shall be monitored for distress ge in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
	•	[ ] TDOT District or Local Maintenance Personnel	
		THP or Local Law Enforcement Personnel	
		[ ] Other:	
1. 0 2. 0 [ ] - Chec [ ] - Chec	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a	on along curb line, both bridge rails and outer edge of bridge deck. ents.	
<u>If Closure is</u>	recommended:		
Coun temp	] - Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.		
[ ] - Conta	act: (1) District Maintenance	Supervisor ( if bridge is State maintained )	
	(2) City or County Highwa	ay Maintenance Official ( if bridge is not State maintained )	
	(3) Tennessee Highway F	Patrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	e Engineer	
	- The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.			
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(423) 757-5152		
CITY ENGINEER'S OFFICE	(423) 757-5115		
POLICE OFFICE	(423) 698-9744		
PUBLIC WORKS DIRECTOR	(423) 757-5152		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and,         as appropriate, photographs of the bridge and stream channel measurements. If significant         scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul> <li>COMMENTS:</li>			
Suggested List of Equipment to conduct the Inspecti	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			
SAFETY HAZARD KEEP	AVVAT		

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24