Rev. 07-24-15		HWAY BRIDGE SCOUR N OF ACTION REPORT	TN TDOT Department of Transportation
BRIDGE ID N	NUMBER: 330A7880001		COUNTY: HAMILTON
BRIDGE	OWNER: CITY OF CHATTANOOGA		ROUTE: 0A788
ROA	D NAME: HOOKER RD		SPECIAL CASE: 0
CR	OSSING: CHATTANOOGA CREEK		COUNTY SEQUENCE: 1
LA	TITUDE:: N 34.99035 DEGREES	S	LOG MILE: 0.44
LON	IGITUDE: W 85.30138 DEGREES	S	YEAR BUILT: 1985
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - MULTIPLE	BEAM OR APPR. SPAN:	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	ENT ON CONCRETE SPREAD FOOTIN	IG FOUNDATION
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
		e in lieu of installing scour count	oridge shall be monitored for distress ermeasures.
		INSPECTION PROCEDURES	
What Initiat	ed the Call-out Inspection?	[ ] BridgeWatch Alert	
		[ ] TDOT District or Loca	I Maintenance Personnel
		[ ] THP or Local Law Enfo	orcement Personnel

## Things to check on a bridge during floods:

- [] Span movement horizontally as well as vertically
  - 1. Check displacement / deflection along curb line, both bridge rails and outer edge of bridge deck.

[] Other:

- 2. Check for plumb of piers or bents.
- [] Check for embankment erosion
- [] Check for drift build-up on piers or bents
- [] Check pier exposure, if possible, and compare to previous inspection
- [] Review the latest bridge inspection report versus current field conditions

## If Closure is recommended:

- [] Stay at bridge with vehicle pulled across road until bridge is secured and properly closed by District, County or City Maintenance Personnel. Use Barricade Tape, traffic cones and/or traffic flares as temporary measures to warn motorists to stay off of the bridge until such time as the bridge may be properly closed and barricaded.
- [ ] Contact: (1) District Maintenance Supervisor ( if bridge is State maintained )
  - (2) City or County Highway Maintenance Official (if bridge is not State maintained)
  - (3) Tennessee Highway Patrol and/or local law enforcement Officers as appropriate
  - (4) TDOT Regional Bridge Engineer
- [] The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.

Ρ	U	В	LI	C	٩T	10	N	D	AT	Έ

07-Nov-24



- [] The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.
- [] The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.

CONTACT PERSONNEL:	<b>TELEPHONE NUMBER:</b>
CITY MAYOR'S OFFICE	(423) 757-5152
CITY ENGINEER'S OFFICE	(423) 757-5115
POLICE OFFICE	(423) 698-9744
PUBLIC WORKS DIRECTOR	(423) 757-5152

[ ] - Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.

## COMMENTS:

Suggested List of Equipment to conduct the Inspection:

Latest Bridge Inspection Report

Scour POA Report with the above Checklist

Bridge Design Plans, if available

Tape measure with weight

Plumb bob

**Range Pole** 

A 1000 Foot Roll of yellow Polyethylene Barricade Tape printed with the following message:

## SAFETY HAZARD KEEP AWAY

A Barricade Tape Dispenser with serrated cutter

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

**TDOT radio directory (State Personnel only)** 

PUBLICATION DATE

07-Nov-24