## **HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT**



COUNTY: HAMILTON

BRIDGE ID NUMBER: 330C9580001

BRIDGE OWNER: HAMILTON COUNTY OFFICIAL

ROAD NAME: BOY SCOUT RD

CROSSING: NORTH CHICKAMAUGA CREEK

ROUTE: **04470** SPECIAL CASE: 0 COUNTY SEQUENCE: 1

	TITUDE:: N 35.17480 DEGREES GITUDE: W 85.22808 DEGREES		
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL CONTINUOUS - STRINGER/I		
		TYPE OF SUBSTRUCTURE	
	NTS: CONCRETE STUB ABUTMENT ON UNKNOWN FOUNDATION		
BENTS:	NOT APPLICABLE		
PIERS:	CONCRETE SOLID SHAFT PIER ON	UNKNOWN FOUNDATION	
		SCOUR EVALUATION	
		our cannot be determined. The bridge shall be monitored for distress e in lieu of installing scour countermeasures.	
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[ ] BridgeWatch Alert	
		[ ] TDOT District or Local Maintenance Personnel	
		[ ] THP or Local Law Enforcement Personnel	
		[ ] Other:	
	neck on a bridge during flood movement - horizontally as w		
		n along curb line, both bridge rails and outer edge of bridge deck.	
2. 0	check for plumb of piers or be	nts.	
[ ] - Checl	k for embankment erosion		
[ ] - Checl	k for drift build-up on piers or	bents	
		nd compare to previous inspection	
[ ] - Revie	w the latest bridge inspection	report versus current field conditions	
lf Closure is	recommended:		
Coun temp	ty or City Maintenance Persor	cross road until bridge is secured and properly closed by District, nnel. Use Barricade Tape, traffic cones and/or traffic flares as rists to stay off of the bridge until such time as the bridge may	
[ ] - Conta	act: (1) District Maintenance S	Supervisor ( if bridge is State maintained )	
	(2) City or County Highwa	y Maintenance Official ( if bridge is not State maintained )	
	(3) Tennessee Highway P	atrol and/or local law enforcement Officers as appropriate	
	(4) TDOT Regional Bridge	•	
	<ul> <li>The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.</li> </ul>		

## **PUBLICATION DATE**

## HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



] - The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route.			
	<ul> <li>The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.</li> </ul>		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(423) 757-5152		
CITY ENGINEER'S OFFICE	(423) 757-5115		
POLICE OFFICE	(423) 698-9744		
PUBLIC WORKS DIRECTOR	(423) 757-5152		
<ul> <li>Summarize and submit findings from the inspection to BridgeWatch scour monitoring system.         The report shall include the date and time of the inspection, a brief summary of findings and,         as appropriate, photographs of the bridge and stream channel measurements. If significant         scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters.</li> </ul>			
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta	pe printed with the following message:		
SAFETY HAZARD KEEP			

**PUBLICATION DATE** 

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

**TDOT radio directory (State Personnel only)** 

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

17-Apr-19