HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 330D6720001

BRIDGE OWNER: CITY OF CHATTANOOGA
ROAD NAME: WATER FRONT DR
CROSSING: BACKWATER OF TN. RIVER

LATITUDE:: N 35.04388 DEGREES
LONGITUDE: W 85.35065 DEGREES

COUNTY: HAMILTON
ROUTE: 0D672
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.21

LON	NGITUDE: W 85.35065 DEGREES	3	YEAR BUILT: 1983	
		TYPE OF SUPERSTRUCTURE		
MAIN SPAN:	STEEL - STRINGER/MULTI-BEAM O	OR GIRDER APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	ENT ON UNKNOWN FOUNDATION		
BENTS:	NOT APPLICABLE			
PIERS:	NOT APPLICABLE			
		SCOUR EVALUATION		
•	unknown foundations. Risk of scr icant flood events. Monitor bridg		bridge shall be monitored for distress ntermeasures.	
		INSPECTION PROCEDURES		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		[] TDOT District or Loca	al Maintenance Personnel	
		[] THP or Local Law En	forcement Personnel	
		[] Other:		
[] - Span 1. C 2. C [] - Chec [] - Chec [] - Revie	Check for plumb of piers or be k for embankment erosion k for drift build-up on piers or k pier exposure, if possible, a ew the latest bridge inspection	ell as vertically n along curb line, both bridg nts. bents nd compare to previous insp		
<u>If Closure is</u>	recommended:			
Coun temp	nty or City Maintenance Persor	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	maintained)			
	(2) City or County Highwa	y Maintenance Official (if b	ridge is not State maintained)	
	(3) Tennessee Highway P	atrol and/or local law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridge	Engineer		
	 The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team. 			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State District maintenance or local highway maintenance officials in establishing a detour route. Any bridge on the selected detour route shall be checked prior to signing the detour route. 			
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
CITY MAYOR'S OFFICE	(423) 757-5152		
CITY ENGINEER'S OFFICE	(423) 757-5115		
POLICE OFFICE	(423) 698-9744		
PUBLIC WORKS DIRECTOR	(423) 757-5152		
 Summarize and submit findings from the inspection to BridgeWatch scour monitoring system. The report shall include the date and time of the inspection, a brief summary of findings and, as appropriate, photographs of the bridge and stream channel measurements. If significant scouring has occurred, the report shall also be copied to Bridge Inspection Headquarters. COMMENTS:			
Suggested List of Equipment to conduct the Inspecti	on:		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Ta			
SAFETY HAZARD KEEP	AVVAT		

PUBLICATION DATE

A roll of Duct Tape

A Barricade Tape Dispenser with serrated cutter

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

Traffic Cones - Minimum of four (4)

07-Nov-24