HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 330D8360001
BRIDGE OWNER: HAMILTON COUNTY
ROAD NAME: MCGILL RD

CROSSING: POSSUM CREEK

LATITUDE:: N 35.33873 DEGREES
LONGITUDE: W 85.12357 DEGREES

COUNTY: HAMILTON
ROUTE: 0D836
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 0.02
YEAR BUILT: 1955

201	1011002: 11 00112001 D2011220		12/1K 26/21: 1335
		TYPE OF SUPERSTRUCTURE	
MAIN SPAN:	STEEL - GIRDER AND FLOORBEAN	SYSTEM APPR. SPAN	NOT APPLICABLE
		TYPE OF SUBSTRUCTURE	
ABUTMENTS:	CONCRETE FULL HEIGHT ABUTME	NT ON UNKNOWN FOUNDATION	
BENTS:	NOT APPLICABLE		
PIERS:	NOT APPLICABLE		
		SCOUR EVALUATION	
Bridge has i	unknown foundations. Risk of soc		e bridge shall be monitored for distress
	ficant flood events. Monitor bridge		
		INSPECTION PROCEDURES	
What Initiated the Call-out Inspection?		[] BridgeWatch Alert	
			cal Maintenance Personnel
			inforcement Personnel
Things to c	heck on a bridge during floods	<u>:</u>	
[] - Span	movement - horizontally as w	ell as vertically	
		•	ge rails and outer edge of bridge deck.
	Check for plumb of piers or be	_	
	k for embankment erosion		
[] - Chec	k for drift build-up on piers or	bents	
	k pier exposure, if possible, ar		pection
	ew the latest bridge inspection	•	
	.	•	
<u>If Closure is</u>	<u>s recommended:</u>		
Cour temp	nty or City Maintenance Persor	nel. Use Barricade Tape, tr	ecured and properly closed by District, raffic cones and/or traffic flares as e until such time as the bridge may
[] - Contact: (1) District Maintena		upervisor (if bridge is Sta	te maintained)
	(2) City or County Highwa	y Maintenance Official (if	bridge is not State maintained)
	(3) Tennessee Highway P	trol and/or local law enfor	cement Officers as appropriate
	(4) TDOT Regional Bridge	Engineer	
] - The Bridge should remain closed until the water recedes and a daylight visual inspection is made by a TDOT bridge inspection team.		

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT

[] - The bridge inspection team will work with State District maintenance or local highway maintenance



officials in establishing a detour route. Ar prior to signing the detour route.	ny bridge on the selected detour route shall be checked			
	The bridge can be re-opened only after a TDOT bridge inspection team checks the substructure units and they are determined to be structurally stable.			
CONTACT PERSONNEL:	TELEPHONE NUMBER:			
COUNTY MAYOR'S OFFICE	(423) 209-6100			
HWY. CHIEF ADMINISTRATOR'S OFFICE	(423) 855-6106			
PUBLIC WORKS DIRECTOR	(423) 209-7899			
COUNTY SHERIFF'S OFFICE	(423) 209-7000			
	and stream channel measurements. If significant so be copied to Bridge Inspection Headquarters.			
Suggested List of Equipment to conduct the Ins	spection:			
Latest Bridge Inspection Report				
Scour POA Report with the above Checklist				
Bridge Design Plans, if available				
Tape measure with weight				
Plumb bob				
Range Pole	In The conducts health the following managers			
A 1000 Foot Roll of yellow Polyethylene Barricae SAFETY HAZARD K				
A Barricade Tape Dispenser with serrated cutter	1			

PUBLICATION DATE

A roll of Duct Tape

Traffic Cones - Minimum of four (4)

TDOT radio directory (State Personnel only)

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

07-Nov-24