HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



BRIDGE ID NUMBER: 350A2540001
BRIDGE OWNER: HARDEMAN COUNTY

ROAD NAME: **WEST RD**CROSSING: **SPRING CREEK**

LATITUDE:: N 35.09790 DEGREES
LONGITUDE: W 89.03627 DEGREES

COUNTY: HARDEMAN
ROUTE: 0A254
SPECIAL CASE: 0
COUNTY SEQUENCE: 1
LOG MILE: 2.16
YEAR BUILT: 1989

LON	IGITUDE: W 89.03627 DEGREE	S	YEAR BUILT: 1989	
MAINI CDANI	DRESTRESSED CONCRETE DOV	TYPE OF SUPERSTRUCTURE	NOT APPLICABLE	
MAIN SPAN:	PRESTRESSED CONCRETE - BOX GIRDERS - SINGLE OR SPREAD	BEAM OR APPR. SPAN:	NOT APPLICABLE	
		TYPE OF SUBSTRUCTURE		
ABUTMENTS:	TMENTS: CONCRETE STUB ABUTMENT ON CONCRETE PILE FOUNDATION			
BENTS:				
PIERS:	CONCRETE HAMMERHEAD PIER ON CONCRETE PILE FOUNDATION			
		SCOUR EVALUATION		
event. Deter			the risk of bridge failure during a flood DOT for assessment. Monitor bridge in lieu	
		 INSPECTION PROCEDURES 		
What Initiated the Call-out Inspection?		[] BridgeWatch Alert		
		• •	al Maintenance Personnel	
		[] THP or Local Law En		
		[] Otner:		
Things to c	heck on a bridge during flood	le•		
_				
	movement - horizontally as v	•	e rails and outer edge of bridge deck.	
	Check for plumb of piers or be		e rails and outer edge of bridge deck.	
	k for embankment erosion	into.		
	k for drift build-up on piers o	· hents		
	• •	nd compare to previous insp	ection	
		n report versus current field c		
[] Kevic	w the latest bridge inspection	Troport versus current neid c		
lf Closure is	recommended:			
Coun temp	ity or City Maintenance Perso	nnel. Use Barricade Tape, tra rists to stay off of the bridge	cured and properly closed by District, ffic cones and/or traffic flares as until such time as the bridge may	
[] - Conta	act: (1) District Maintenance	Supervisor (if bridge is State	maintained)	
	(2) City or County Highw	ay Maintenance Official (if b	ridge is not State maintained)	
	(3) Tennessee Highway F	Patrol and/or local law enforce	ement Officers as appropriate	
	(4) TDOT Regional Bridg	e Engineer	-	
	Bridge should remain closed until the water recedes and a daylight visual inspection is made FDOT bridge inspection team.			

PUBLICATION DATE

HIGHWAY BRIDGE SCOUR PLAN OF ACTION REPORT



 The bridge inspection team will work with State I officials in establishing a detour route. Any bridg prior to signing the detour route. 			
[] - The bridge can be re-opened only after a TDOT be units and they are determined to be structurally struc	e can be re-opened only after a TDOT bridge inspection team checks the substructure they are determined to be structurally stable.		
CONTACT PERSONNEL:	TELEPHONE NUMBER:		
COUNTY MAYOR'S OFFICE	(731) 658-3266		
HWY. CHIEF ADMINISTRATOR'S OFFICE	(731) 658-5102		
COUNTY SHERIFF'S OFFICE	(731) 658-3971		
The report shall include the date and time of the i as appropriate, photographs of the bridge and strescouring has occurred, the report shall also be constant.	ream channel measurements. If significant		
COMMENTS:			
Suggested List of Equipment to conduct the Inspection	<u>ı:</u>		
Latest Bridge Inspection Report			
Scour POA Report with the above Checklist			
Bridge Design Plans, if available			
Tape measure with weight			
Plumb bob			
Range Pole			
A 1000 Foot Roll of yellow Polyethylene Barricade Tape	printed with the following message:		
SAFETY HAZARD KEEP AV	NAY		
A Barricade Tape Dispenser with serrated cutter			
A roll of Duct Tape			
Traffic Cones - Minimum of four (4)			

PUBLICATION DATE

Traffic Safety Flares - Minimum of four (4) or set of electronic warning flashers

TDOT two-way radio (State Personnel only) and/or cellular telephone

TDOT radio directory (State Personnel only)